Remote Type
Pressure Sensors/
Pressure Sensor Controllers

Compact Pneumatic Pressure Sensor
PSE530 ▸p. 5

Analog Output



Compact Pneumatic Pressure Sensor/Switch
PSE540 ▸p. 9



Analog Output
Switch Output
IO-Link

Low Differential Pressure Sensor
PSE550 ▸p. 17

Analog Output



Pressure Sensor for General Fluids
PSE560 ▸p. 20

Analog Output



Pressure Sensor/Switch for General Fluids
PSE570 ▸p. 23



Analog Output
Switch output
IO-Link

3-Screen Display
Multi-channel Digital Sensor Monitor
PSE200A ▸p. 32



3-Screen Display
Sensor Monitor
PSE300A ▸p. 44



3-Screen Display
Sensor Monitor
PSE300AC ▸p. 54



New PSE Sensor Set Up Tool
PSE-ST ▸p. 58-1



***PSE* Series**


SMC

CAT.ES100-56D Ⓐ

IO-Link Compatible

Two types of connection are supported depending on the application.

- For the communication of sensor data/Reduced installation space ➡ Direct connection **PSE54□-L/PSE57□-L2**
- On site setting and the confirmation of measured values/Reduced wiring ➡ Hub connection **PSE202A/203A**



Compatible Series PSE54□-L / PSE57□-L2 p. 11, 25

Visualization of operation/equipment status/Remote monitoring and control by communication

Implement diagnostic bits in the process data.

The diagnostic bit in the cyclic process data makes it easy to find problems with the equipment. It is possible to find problems with the equipment in real time using the cyclic (periodic) data and to monitor such problems in detail with the noncyclic (aperiodic) data.

Process Data

Bit offset	Item	Note	
0	OUT1 output	0: OFF	1: ON
1	OUT2 output	0: OFF	1: ON
8	Diagnosis (Measurement)	0: Normal	1: Abnormal
14	Diagnosis (Error)	0: Normal	1: Abnormal
15	Diagnosis (Error)	0: Normal	1: Abnormal
16 to 31	Measured pressure value	Signed 16 bit	

Diagnosis items
Outside of rated pressure range
Internal product malfunction
· Over current · Outside of zero-clear range · IO-Link master version error · Snapshot failure



IO-Link Compatible Device
PSE54□-L / PSE57□-L2

Bit offset	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16
Item	Measured pressure value (PD)															

Bit offset	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Item	System error	Other than system error	Reservation					Measurement	Reservation						OUT2	OUT1
	Diagnosis							Diagnosis							Switch output	

Compatible with Switch Output Specification

A compact pressure sensor supports switch output specification.

- **Factory setting** ➡ **PSE54□-N/P, PSE57□-A/B**
- **Setup using the PSE sensor set up tool with IO-Link specification** ➡ **PSE54□-L, PSE57□-L2 + PSE-ST**

Switch output specification based on factory settings


If switch setting specifications are determined in advance

- Is there more than one sensor with the same settings in the same equipment?
- Are there repeat devices equipped with sensors with the same settings?
- Is there a sensor that needs its settings at the equipment shipping destination to be tamper proof?

Compatible Series



PSE54□-N/P PSE57□-A/B



Switch output specification using the PSE sensor set up tool (configurable) with IO-Link specification

If switch setting specifications vary by device


Compatible Series



PSE54□-L PSE57□-L2 + PSE-ST


- The IO-Link specification can be used as a switch output when the IO-Link master connected to set as the switch output (SIO), or when connecting to a digital input unit (without connecting to the IO-Link master).

➡This is used as a switch output when using the PSE sensor set up tool, and connecting and setting up the sensor in advance.



∗ Connect and set up in advance. Do not connect after setting.


- Standardization of inventory




(∗ Example of pressure settings)

Benefits for existing pressure sensors/switches

Analog output PSE54□/PSE57□ series + Sensor monitor PSE300A series



Space saving
(Elimination of sensor monitors)



Integrated display pressure switch ZSE20/ISE20 series, ISE7□/ISE7□G series

Compact: 84% reduction[*1] (Occupied volume ratio: 37530 mm^3 ➡ 6048 mm^3)
Lightweight: 68% reduction[*1] (Weight: 34 g ➡ 11 g)
(Elimination of displays)



*1 R1/8 piping, Does not include lead wire



Compact: 68% reduction[*2] (Occupied volume ratio: 131213 mm^3 ➡ 41350 mm^3)
Lightweight: 44% reduction[*2] (Weight: 184 g ➡ 103 g)
(Elimination of displays)




*2 10 MPa type, 1/4 piping, Does not include lead wire



Benefits for existing pressure sensors/switches

Air checker: Pressure switch PS1000 series



Value setting
Expanded piping variations


Value setting
Compatible with general fluids
IP65 enclosure
(* Sensor unit only)




PS1000

Compatible with small switches for general fluids

Application Example **For hydraulic cylinder pressure control**



PSE57□-A/B



PSE Series Variations

	Pressure Sensors					Digital Sensor Monitors		
Model	**PSE530**	**PSE540**	**PSE550**	**PSE560**	**PSE570**	**PSE200A**	**PSE300A**	**PSE300AC**
								
	p. 5	p. 9	p. 17	p. 20	p. 23	p. 32	p. 44	p. 54
Basic Specifications								
Applicable fluid	Air			General fluids				
Rated pressure range (Min. display)								
Repeatability	±1 % (F.S.)	±0.2 % (F.S.)	±0.3 % (F.S.)	±0.2 % (F.S.)	±0.2% (F.S.) PSE570/573/574 ±0.5% (F.S.) PSE575/576/577	±0.1 % (F.S.)		
Voltage	12 to 24 VDC							
No. of outputs for switch		1 output*1			2 outputs*1	5 outputs	2 outputs	2 outputs
IO-Link		○*1			○*1	○		
Analog output	1 to 5 V		1 to 5 V 4 to 20 mA				1 to 5 V 4 to 20 mA	
Functions								
Digital display						2-color	2-color	2-color
Enclosure	IP40			IP65		Front face: IP65 Others: IP40	IP40	IP65
Wiring	Connector	Grommet			Connector	Connector		
Main functions (Settings)						IO-Link compatible 3-screen display Panel mounting possible Display value fine adjustment function	3-screen display Panel mounting possible Display value fine adjustment function Anti-chattering function	3-screen display Display value fine adjustment function Selectable pressure unit
Others								
Connection thread	M, Reducer	M, R, NPT, Reducer	Resin piping	R, NPT, Rc, URJ, TSJ*2	R			
Int'l standards	CE/UKCA	CE/UKCA, UL, CSA			CE/UKCA, UL, CSA*3	CE/UKCA	CE/UKCA, UL, CSA	CE/UKCA
Wiring: e-con	●	●	●	●	●	●	●	
Wiring: Flexible cable		●	●					
Mounting: Direct	●	●	●	●	●		●	●
Mounting: With bracket			●				●	
Mounting: Panel mount						●	●	
Mounting: DIN rail								

*1 The IO-Link compatible switch output specification cannot be connected to the PSE200A/PSE300A(C).
*2 URJ: Face seal fitting, TSJ: Compression fitting *3 Excludes the IO-Link/2-output type

Pressure Sensor/*PSE5□□ Series*

	Rated pressure range	PSE53□	PSE54□	PSE55□	PSE56□	PSE57□
						
Vacuum	−101 kPa – 0	PSE531	PSE541	—	PSE561	—
Compound pressure	−100 kPa – 100 kPa	PSE533	PSE543	—	PSE563	PSE573
Positive pressure	0 – 100 kPa	PSE532	—	—	—	—
	0 – 500 kPa	—	—	—	PSE564	PSE574
	0 – 1 MPa	PSE530	PSE540	—	PSE560	PSE570
	0 – 2 MPa	—	—	—	—	PSE575
	0 – 5 MPa	—	—	—	—	PSE576
	0 – 10 MPa	—	—	—	—	PSE577
Low differential pressure	0 – 2 kPa	—	—	PSE550	—	—

Digital Sensor Monitor/*PSE200A/300A Series*

	PSE200A	PSE300A	PSE300AC
			
Applicable pressure sensor model*1	Display/Smallest settable increment		
PSE531 / PSE541 / — / PSE561 / —	0.1 kPa	0.1 kPa	0.1 kPa
PSE533 / PSE543 / — / PSE563 / PSE573	0.1 kPa	0.1 kPa	0.1 kPa
PSE532 / — / — / — / —	0.1 kPa	0.1 kPa	0.1 kPa
— / — / — / PSE564 / PSE574	1 kPa	1 kPa	1 kPa
PSE530 / PSE540 / — / PSE560 / PSE570	0.001 MPa	0.001 MPa	0.001 MPa
— / — / PSE550 / — / —	0.001 kPa	0.001 kPa	0.001 kPa

* Analog output only

Main Functions * For details, refer to the "Operation Manual" on the SMC website.

Key-lock	Locks the keys to prevent accidental operation
Peak/Bottom value holding	Displays the min. and max. values being set and keeps those values on the display
Auto-preset	Allows for the pressure to be set automatically In the case of suction verification, it memorizes the pressure when adsorbed and released. After repeating several times, the optimum values are calculated automatically.
Auto-shift	Stable switch output is possible even when the supply pressure fluctuates. The set value is corrected automatically in accordance with the fluctuations in the supply pressure.
Display value fine adjustment	Allows for the displayed values to be adjusted (±5%) and the evening out of the variations in the displayed values of each pressure switch
Anti-chattering	Prevents malfunction due to sharp pressure fluctuations The detection of momentary pressure fluctuation as abnormal pressure can be prevented by changing the response time settings.




Compact Pneumatic Pressure Sensor

PSE530 Series

Series	Rated pressure range
	−100 kPa / 0 / 100 kPa / 500 kPa / 1 MPa
PSE530	0 — 1 MPa
PSE531	−101 kPa — 0
PSE532	0 — 101 kPa
PSE533	−101 kPa — 101 kPa


Connector type



Application example

Leak test of radiator

PSE532 + PSE300A Series



Low pressure sensor (PSE532-□) is used to detect minute differentiations.
Auto-shift function reduces influence of fluctuations in the supply pressure.

Applications

Pressure Sensor
PSE530 Series



How to Order

PSE53 0 – M5 – □



Sensor range

0	Positive pressure [0 to 1 MPa]
1	Vacuum [0 to –101 kPa]
2	Low pressure [0 to 101 kPa]
3	Compound pressure [–101 to 101 kPa]

Port size

M5	M5 x 0.8
R06	ø6 reducer
R07	1/4 inch reducer

Option

Nil	None
L	Sensor cable (3 m) 
C2L	Connector for pressure sensor controller (1 pc.) + Sensor cable (3 m) 

∗ The connector is not attached to the cable, but is included with the shipment.

Options/Part Nos.

When only optional parts are required, order with the part numbers listed below.

Description	Part no.	Note
Connector for pressure sensor controller	ZS-28-C	1 pc. per set
Sensor cable	ZS-26-F	Cable length: 3 m
Connector for pressure sensor controller + Sensor cable	ZS-26-J	Cable length: 3 m The connector is not attached to the cable at the time of shipment.

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Specifications


Model		**PSE530** (Positive pressure)	**PSE531** (Vacuum)	**PSE532** (Low pressure)	**PSE533** (Compound pressure)
Rated pressure range		0 to 1 MPa	0 to –101 kPa	0 to 101 kPa	–101 to 101 kPa
Extension analog output range		–0.1 to 0 MPa	10.1 to 0 kPa	–10.1 to 0 kPa	—
Proof pressure		1.5 MPa	500 kPa		
Applicable fluid		Air/Non-corrosive gas/Non-flammable gas			
Power supply voltage		12 to 24 VDC ±10%, Ripple (p-p) 10% or less (with reverse connection protection)			
Current consumption		15 mA or less (with no load)			
Output specifications		Analog output 1 to 5 V (within rated pressure range), 0.6 to 1 V (within extension analog output range), Output impedance: Approx. 1 kΩ			
Accuracy (Ambient temperature at 25°C)		±2% F.S. (within rated pressure range), ±5% F.S. (within extension analog output range)			
Linearity		±1% F.S.			
Repeatability		±1% F.S.			
Power supply voltage effect		±1% F.S. based on the analog output at 18 V ranging from 12 to 24 VDC			
Environment	**Enclosure**	IP40			
	Temperature range	Operating: 0 to 50°C; Stored: –10 to 70°C (No freezing or condensation)			
	Withstand voltage	1000 VAC (in 50/60 Hz) for 1 min between terminals and housing			
	Insulation resistance	5 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing			
Temperature characteristics		±2% F.S. (25°C reference)			
Sensor cable/Option		Halogen-free heavy-duty cable, 3 cores, ø2.7, 3 m, Conductor area: 0.15 mm², Insulator O.D.: 0.8 mm			
Standards		CE/UKCA marking			

Piping Specifications

Part no.		**M5**	**R06**	**R07**
Port size		M5 x 0.8 male thread	ø6 reducer type	1/4 inch reducer type
Materials of parts in contact with fluid		Pressure sensor: Silicon, O-ring: NBR		
		Body: Stainless steel 304	Body: PBT	
Weight	**With sensor cable (3 m)**	41 g	38 g	
	Without sensor cable	7 g	3.8 g	


Internal Circuit and Wiring Example

PSE53□
Voltage output type
1 to 5 V
Output impedance
Approx. 1 kΩ



Analog Output


1 to 5 VDC




Range	Rated pressure range	A	B	C
For vacuum	0 to −101 kPa	0	−101 kPa	10.1 kPa
For compound pressure	−101 kPa to 101 kPa	−101 kPa	101 kPa	—
For low pressure	0 to 101 kPa	0	101 kPa	−10.1 kPa
For positive pressure	0 to 1 MPa	0	1 MPa	−0.1 MPa

Dimensions

PSE53□-M5




PSE53□-R06 / R07



[mm]

Model	Applicable fitting size (**D**)
PSE53□-R06	6
PSE53□-R07	1/4"

With sensor cable



Digital Sensor Monitors							
PSE300AC	PSE300A	PSE200A	PSE570	PSE560	PSE550	PSE540	PSE530




Compact Pneumatic Pressure Sensor/Switch

PSE540 Series


Series	Rated pressure range
	–100 kPa / 0 / 100 kPa / 500 kPa / 1 MPa
PSE540	0 — 1 MPa
PSE541	–101 kPa — 0
PSE543	–100 kPa — 100 kPa

- **Weight: 2.9 g**
- **Head size: 9.6 x 20.8 x 18 mm**




For PSE54□-M3


Application examples



Pads can be directly mounted.



Manifolding is possible.



Applications

Compact Pneumatic Pressure Sensor/Switch

PSE540 Series

RoHS

Analog output type

IO-Link / 1-output type ▶ p. 11



How to Order


Sensor range

0	Positive pressure [0 to 1 MPa]
1	Negative pressure [0 to –101 kPa]
3	Compound pressure [–100 to 100 kPa]

Accuracy

Nil	±2% F.S.
A	±1% F.S.

Option (Connector)

Nil	None
C2	Connector for pressure sensor controller (1 pc.) 

PSE54 1 □ – M3 – □

Port size

M3	M3 x 0.5	
M5	M5 x 0.8	
01	R1/8 (with M5 female thread)	
N01	NPT1/8 (with M5 female thread)	
R04	ø4 reducer	
R06	ø6 reducer	

IM5	M5 female thread, through type	
IM5H	M5 female thread, through type (with mounting hole)	

∗ The connector is not attached to the cable, but is included with the shipment.

Option/Part No.

Description	Part no.	Note
Connector for pressure sensor controller	ZS-28-C	1 pc.

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Specifications

Model		PSE540	PSE541	PSE543
Rated pressure range		0 to 1 MPa	0 to –101 kPa	–100 to 100 kPa
Extension analog output range		–0.1 to 0 MPa	10.1 to 0 kPa	—
Proof pressure		1.5 MPa	500 kPa	
Applicable fluid		Air/Non-corrosive gas/Non-flammable gas		
Power supply voltage		12 to 24 VDC ±10%, Ripple (p-p) 10% or less (with reverse connection protection)		
Current consumption		15 mA or less		
Output specifications		Analog output 1 to 5 V (within rated pressure range), 0.6 to 1 V (within extension analog output range), Output impedance: Approx. 1 kΩ		
Accuracy (Ambient temperature at 25°C)		PSE54□: ±2% F.S. (within rated pressure range), ±5% F.S. (within extension analog output range) PSE54□A: ±1% F.S. (within rated pressure range), ±3% F.S. (within extension analog output range)		
Linearity		±0.7% F.S. or less	±0.4% F.S.	
Repeatability		±0.2% F.S.		
Power supply voltage effect		±0.8% F.S.		
Environment	**Enclosure**	IP40		
	Operating temperature range	Operating: 0 to 50°C, Stored: –20 to 70°C (No freezing or condensation)		
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)		
	Withstand voltage	1000 VAC (in 50/60 Hz) for 1 min between terminals and housing		
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing		
Temperature characteristics		±2% F.S. (25°C reference)		
Sensor cable		Oilproof heavy-duty vinyl cable (ellipse), 3 cores, 2.7 x 3.2, 3 m, Conductor area: 0.15 mm², Insulator O.D.: 0.9 mm		
Standards		CE/UKCA marking, UL/CSA (E216656)		


Piping Specifications

Part no.		M3	M5	01	N01	R04	R06	IM5	IM5H
Port size		M3 x 0.5	M5 x 0.8	R1/8 M5 x 0.8	NPT1/8 M5 x 0.8	ø4 reducer	ø6 reducer	M5 female thread, through type	M5 female thread, through type (with mounting hole)
Material	**Case**	Resin case: PBT Fitting: Stainless steel 303		Resin case: PBT Fitting: C3604BD		PBT		Resin case: PBT Fitting: A6063S-T5	
	Pressure sensing section	Pressure sensor: Silicon, O-ring: NBR							
Weight	**With sensor cable**	42.4 g	42.7 g	49.3 g		41.4 g	41.6 g	43.3 g	44.1 g
	Without sensor cable	2.9 g	3.2 g	9.8 g		1.9 g	2.1 g	3.8 g	4.6 g

Compact Pneumatic Pressure Sensor/Switch

PSE540 Series

IO-Link / 1-output type



Analog output type ▶ p. 10

How to Order

Sensor range

0	Positive pressure [0 to 1 MPa]
1	Negative pressure [0 to –101 kPa]
3	Compound pressure [–100 to 100 kPa]

Accuracy

Nil	±2% F.S.
A	±1% F.S.

Output specification

L	IO-Link/Switch: 1 output (PNP or NPN switching type for switch output)

IO-Link: PSE54 1 □ – M3 – L □

Switch output: PSE54 1 □ – M3 – N □ – □ (❶ ❷)

Port size

M3	M3 x 0.5	
M5	M5 x 0.8	
01	R1/8 (with M5 female thread)	
N01	NPT1/8 (with M5 female thread)	
R04	ø4 reducer	
R06	ø6 reducer	
IM5	M5 female thread, through type	
IM5H	M5 female thread, through type (with mounting hole)	

Output specification

N	NPN open collector 1 output
P	PNP open collector 1 output

❶ Lead wire termination

Nil	Basic	
S	With M12-4 pin connector, 500 mm	

❷ Set value (When output specification "N" or "P" is selected)


P 005 5

- P: OUT1 output type
- 005: OUT1 set value (P1/n1)
- 5: OUT1 hysteresis (H1)

P	Normal output
N	Reversed output


Normal output

Switch output



Reversed output

Switch output



SMC

OUT1 set value (P1/n1)

Symbol	Sensor range		
	PSE540	**PSE541**	**PSE543**
-10			–100 kPa∗1
-09			–90 kPa
-08			–80 kPa
-07			–70 kPa
-06			–60 kPa
-05			–50 kPa
-04			–40 kPa
-03			–30 kPa
-02			–20 kPa
-01	–0.1 MPa∗1	10 kPa∗1	–10 kPa
000	0.0 MPa	0 kPa	0 kPa
001	0.1 MPa	–10 kPa	10 kPa
002	0.2 MPa	–20 kPa	20 kPa
003	0.3 MPa	–30 kPa	30 kPa
004	0.4 MPa	–40 kPa	40 kPa
005	0.5 MPa	–50 kPa	50 kPa
006	0.6 MPa	–60 kPa	60 kPa
007	0.7 MPa	–70 kPa	70 kPa
008	0.8 MPa	–80 kPa	80 kPa
009	0.9 MPa	–90 kPa	90 kPa
010	1.0 MPa∗1	–100 kPa∗1	100 kPa∗1

OUT1 hysteresis (H1)

Symbol	Sensor range		
	PSE540	**PSE541**	**PSE543**
0	0.00 MPa	0 kPa	0 kPa
1	0.01 MPa	1 kPa	1 kPa
2	0.02 MPa	2 kPa	2 kPa
3	0.03 MPa	3 kPa	3 kPa
4	0.04 MPa	4 kPa	4 kPa
5	0.05 MPa	5 kPa	5 kPa
6	0.06 MPa	6 kPa	6 kPa
7	0.07 MPa	7 kPa	7 kPa
8	0.08 MPa	8 kPa	8 kPa
9	0.09 MPa	9 kPa	9 kPa
A	0.10 MPa	10 kPa	10 kPa

∗1 Part numbers whose switch output switching point is out of the set pressure range cannot be selected.
Normal output: P1 - H1 ≥ set pressure range lower limit (for PSE540, PSE543),
P1 + H1 ≥ set pressure range lower limit (for PSE541)
Reverse output: n1 + H1 ≤ set pressure range upper limit (for PSE540, PSE543),
n1 - H1 ≤ set pressure range upper limit (for PSE541)
Be sure to confirm the above.

∗2 If you wish to use a set value other than the above, contact your local SMC sales representative.

Ordering Example

- **Pressure range: Positive pressure**
- **Port size: M3**
- **Accuracy: ±2% F.S.**
- **Output specification: NPN open collector 1 output**
- **Lead wire termination: With M12-4 pin connector**
- **OUT1: Normal output, Set point 0.5 MPa, Hysteresis 0.05 MPa**

PSE540-M3-NS-P0055

Specifications

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

		IO-Link		
Model		**PSE540(A)-□-L**	**PSE541(A)-□-L**	**PSE543(A)-□-L**
Rated pressure range		–0.100 to 1.000 MPa	0.0 to –101.0 kPa	–100.0 to 100.0 kPa
Set pressure range		–0.105 to 1.050 MPa	10.0 to –105.0 kPa	–105.0 to 105.0 kPa
Smallest settable increment		0.001 MPa	0.1 kPa	0.1 kPa
Proof pressure		1.5 MPa	500 kPa	
Applicable fluid		Air/Non-corrosive gas/Non-flammable gas		
Power supply voltage	**When used as a switch output device (When not used as an IO-Link device)**	12 to 24 VDC ±10%, Ripple (p-p) 10% or less		
	When used as an IO-Link device	18 to 26.4 VDC, including ripple (p-p) 10%		
Current consumption		35 mA or less		
Output		NPN or PNP open collector 1 output (Selectable) Hysteresis, Window comparator, Error output Normal, Reversed Max. load current: 80 mA Max. applied voltage: 30 V Internal voltage drop (Residual voltage): 1.5 V or less (at load current of 80 mA) Delay time: 3.4 ms or less, Variable from 0 to 60 s/0.01 s increments		
Accuracy (Ambient temperature at 25°C)		PSE54□A: ±1% F.S. (within rated pressure range), ±3% F.S. (within extension analog output range) PSE54□: ±2% F.S. (within rated pressure range), ±5% F.S. (within extension analog output range)		
Linearity		±0.7% F.S.	±0.4% F.S.	
Repeatability		±0.2% F.S.		
Power supply voltage effect		±0.8% F.S.		
Environment	**Enclosure**	IP40		
	Operating temperature range	Operating: 0 to 50°C, Stored: –10 to 60°C (No freezing or condensation)		
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)		
	Withstand voltage	1000 VAC (in 50/60 Hz) for 1 min between terminals and housing		
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing		
Temperature characteristics		±2% F.S. (25°C reference)		
Sensor cable		Oilproof heavy-duty vinyl cable (ellipse), 3 cores, 2.7 x 3.2, 3 m, Conductor area: 0.15 mm², Insulator O.D.: 0.9 mm		
Standards		CE/UKCA marking, UL/CSA (E216656)		

Communication	**IO-Link type**	Device
	IO-Link version	V1.1
	Communication speed	COM2 (38.4 kbps)
	Configuration file	IODD file
	Min. cycle time	3.4 ms
	Process data length	Input data: 4 bytes, Output data: 0 bytes
	On request data communication	Yes
	Data storage function	Yes
	Event function	Yes
	Vendor ID	131 (0 x 0083)
	Indicator light	SIO mode: Lights up when switch output is turned ON (OUT1: Red) IO-Link communication: ON or flashing (OUT1: Red)

Specifications

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Model			Switch output		
			PSE540(A)-□-N/P	**PSE541(A)-□-N/P**	**PSE543(A)-□-N/P**
Rated pressure range∗1			–0.100 to 1.000 MPa	0.0 to –101.0 kPa	–100.0 to 100.0 kPa
Set pressure range∗1			–0.105 to 1.050 MPa	10.0 to –105.0 kPa	–105.0 to 105.0 kPa
Smallest settable increment∗1			0.001 MPa	0.1 kPa	0.1 kPa
Proof pressure			1.5 MPa	500 kPa	
Applicable fluid			Air/Non-corrosive gas/Non-flammable gas		
Power supply voltage			12 to 24 VDC ±10%, Ripple (p-p) 10% or less		
Current consumption			35 mA or less		
Output			NPN or PNP open collector 1 output Hysteresis Normal, Reversed Max. load current: 80 mA Max. applied voltage: 30 V Internal voltage drop (Residual voltage): 1.5 V or less (at load current of 80 mA) Delay time: 3.4 ms or less		
Accuracy (Ambient temperature at 25°C)			PSE54□A: ±1% F.S. (within rated pressure range), ±3% F.S. (within extension analog output range) PSE54□: ±2% F.S. (within rated pressure range), ±5% F.S. (within extension analog output range)		
Linearity			±0.7% F.S.	±0.4% F.S.	
Repeatability			±0.2% F.S.		
Power supply voltage effect			±0.8% F.S.		
Environment	**Enclosure**		IP40		
	Operating temperature range		Operating: 0 to 50°C, Stored: –10 to 60°C (No freezing or condensation)		
	Operating humidity range		Operating/Stored: 35 to 85% RH (No condensation)		
	Withstand voltage		1000 VAC (in 50/60 Hz) for 1 min between terminals and housing		
	Insulation resistance		50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing		
Temperature characteristics			±2% F.S. (25°C reference)		
Sensor cable			Oilproof heavy-duty vinyl cable (ellipse), 3 cores, 2.7 x 3.2, 3 m, Conductor area: 0.15 mm², Insulator O.D.: 0.9 mm		
Standards			CE/UKCA marking, UL/CSA (E216656)		


∗1 Should you require settings other than those specified by the model indication method, please contact our sales representative.

Piping Specifications

Part no.		**M3**	**M5**	**01**	**N01**	**R04**	**R06**	**IM5**	**IM5H**
Port size		M3 x 0.5	M5 x 0.8	R1/8 M5 x 0.8	NPT1/8 M5 x 0.8	ø4 reducer	ø6 reducer	M5 female thread, through type	M5 female thread, through type (with mounting hole)
Material	**Case**	Resin case: PC Fitting: Stainless steel 303		Resin case: PC Fitting: C3604BD		Resin case: PC		Resin case: PC Fitting: A6063S-T5	
	Pressure sensing section	Pressure sensor: Silicon, O-ring: NBR							
Weight	**With sensor cable**	43.6 g	43.9 g	50.5 g		42.6 g	42.8 g	44.5 g	45.3 g
	Without sensor cable	4.1 g	4.4 g	11 g		3.1 g	3.3 g	5.0 g	5.8 g


Internal Circuit and Wiring Example

PSE54□
Voltage output type
1 to 5 V
Output impedance
Approx. 1 kΩ




Analog Output

1 to 5 VDC




Range	Rated pressure range	A	B	C
For vacuum	0 to –101 kPa	0	–101 kPa	10.1 kPa
For compound pressure	–100 kPa to 100 kPa	–100 kPa	100 kPa	—
For positive pressure	0 to 1 MPa	0	1 MPa	–0.1 MPa

-N
NPN (1 output)




-P
PNP (1 output)




-L: (IO-Link/Switch 1 output)

When used as a switch output device (When not used as an IO-Link device = When in SIO mode)


NPN open collector 1 output setting



PNP open collector 1 output setting




When used as an IO-Link device




IO-Link: Process Data

Relationship between the process data and pressure value


PSE540-L (For positive pressure)



PSE541-L (For negative pressure)




PSE543-L (For compound pressure)




Dimensions

PSE54□- M3 / M5









[mm]

	PSE54□-M3	PSE54□-M5
A	10.8	11.5
B	3	3.5

PSE54□- R04 / R06








[mm]


	PSE54□-R04	PSE54□-R06
A	ø4	ø6
B	18	20


Common Dimensions



PSE54□-IM5









PSE54□- 01 / N01









PSE54□-IM5H









Low Differential Pressure Sensor


PSE550 Series

Series	Rated pressure range
	0 — 1 kPa — 2 kPa
PSE550	0 — 2 kPa

Power LED status indicator



2 mounting types



Mounting directly


Mounting with bracket

Accuracy
±1% F.S.

Proof pressure
65 kPa


Application examples

Flow control
PSE550 Series




Can control air flow by monitoring the flow rate inside the duct.

Filter clogging monitoring
PSE550 Series



Can control filtration and replacement periods by monitoring the clogging of the filter.

Liquid level detection
PSE550 Series



Can detect the liquid level through changes in the purge pressure.

Applications

Low Differential Pressure Sensor
PSE550 Series




How to Order

PSE550 – □ – □ □

Output specifications


Nil	Voltage output type 1 to 5 V
28	Current output type 4 to 20 mA

Option 2 (Connector)

Nil	None
C2	Connector for pressure sensor controller (1 pc.) 

∗ The connector is not attached to the cable, but is included with the shipment.

Option 1 (Bracket)

Nil	None
A	Bracket 

∗ The bracket is not attached to the product, but is included with the shipment.

Options/Part Nos.

Description	Part no.	Note
Bracket	ZS-30-A	With M3 x 5 L (2 pcs.)
Connector for pressure sensor controller	ZS-28-C	1 pc.

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.


Specifications

Model		PSE550	PSE550-28
Rated differential pressure range		0 to 2 kPa	
Operating pressure range		–50 to 50 kPa∗1	
Extension analog output range		–0.2 to 0 kPa	—
Proof pressure		65 kPa	
Applicable fluid		Air/Non-corrosive gas/Non-flammable gas	
Power supply voltage		12 to 24 VDC ±10%, Ripple (p-p) 10% or less (with reverse connection protection)	
Current consumption		15 mA or less	—
Output specifications		Analog output: 1 to 5 VDC (within rated differential pressure range) 0.6 to 1 VDC (within extension analog output range) Output impedance: Approx. 1 kΩ	Analog output: 4 to 20 mA DC (within rated differential pressure range) Maximum load impedance: 500 Ω or less (at 24 VDC) 100 Ω or less (at 12 VDC)
Accuracy (Operating temperature at 25°C)		±1% F.S. (within rated differential pressure range), ±3% F.S. (within extension analog output range)	
Linearity		±0.5% F.S.	
Repeatability		±0.3% F.S.	
Indicator light		Orange light is turned on. (When energized)	
Environment	**Enclosure**	IP40	
	Operating temperature range	Operating: 0 to 50°C, Stored: –20 to 70°C (No freezing or condensation)	
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)	
	Withstand voltage	1000 VAC (in 50/60 Hz) for 1 min between terminals and housing	
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing	
Temperature characteristics		±3% F.S. (25°C reference)	
Port size		ø4.8 (ø4.4 in the end) resin piping (Applicable to I.D. ø4 air tubing)	
Materials of parts in contact with fluid		Resin pipe: Nylon, Piston area of sensor: Silicon	
Sensor cable		Oilproof heavy-duty vinyl cable, 3 cores, ø2.6, 3 m Conductor area: 0.15 mm², Insulator O.D.: 0.9 mm	Oilproof heavy-duty vinyl cable, 2 cores, ø2.6, 3 m Conductor area: 0.15 mm², Insulator O.D.: 0.9 mm
Weight	**With sensor cable**	75 g	
	Without sensor cable	35 g	
Standards		CE/UKCA marking, UL/CSA (E216656)	


∗1 Can detect differential pressure from 0 to 2 kPa within the range of –50 to 50 kPa.

Internal Circuits and Wiring Examples

PSE550
Voltage output type
1 to 5 V
Output impedance
Approx. 1 kΩ




PSE550-28
Current output type
4 to 20 mA
Allowable load impedance
500 Ω or less (at 24 VDC)
100 Ω or less (at 12 VDC)




* Install the load either on the LINE (+) or LINE (–) side.

Analog Output


1 to 5 VDC





4 to 20 mA DC




Dimensions










With bracket







A View



Pressure Sensor for General Fluids

PSE560 Series

Series	Rated pressure range
	−100 kPa / 0 / 100 kPa / 500 kPa / 1 MPa
PSE560	0 to 1 MPa
PSE561	−101 kPa to 0
PSE563	−100 kPa to 100 kPa
PSE564	0 to 500 kPa

Applicable fluid examples

- Argon
- Air-containing drainage
- Refrigerant
- Nitrogen
- Hydraulic oil
- Silicone oil
- Water
- Carbon dioxide
- Lubricant
- Fluorocarbon
- Air

Material of parts in contact with fluid: Stainless steel 316L

IP65

Copper-free Fluorine-free

Oil-free (Single diaphragm construction)


Variations

Port type	Thread type	Special fitting type for semiconductors
Port size	R1/8, R1/4, Rc1/8, NPT1/8, NPT1/4	URJ1/4, TSJ1/4∗1
Leakage	1 x 10^{-5} Pa·m^3/s	1 x 10^{-10} Pa·m^3/s
Analog output	1 to 5 V voltage output	
	4 to 20 mA current output	


∗1 For URJ1/4, TSJ1/4, refer to “Glossary of Terms/Technical Information” in the **Web Catalog**.

Application examples


Cleaning lines



Check for working pressure for hydraulic cylinders



Suction verification of workpieces containing moisture



∗ When vacuum is released, take precautions to avoid water hammer. (An adapter with restrictor (ZS-31-X175) is available to prevent water hammer.) (Refer to “NOTE” in the Operation Manual on the SMC website for details.)

Applications

Pressure Sensor for General Fluids

PSE560 Series




How to Order

Sensor range

0	Positive pressure [0 to 1 MPa]
1	Vacuum [0 to –101 kPa]
3	Compound pressure [–100 to 100 kPa]
4	Positive pressure [0 to 500 kPa]

Option (Connector)

Nil	None
C2	Connector for pressure sensor controller (1 pc.) 

* Current output type cannot be connected to the PSE200 series.
* The connector is not attached to the cable, but is included with the shipment.

PSE56 0 – 01 – □ – □

Port size

01	R1/8 (with M5 female thread)
02	R1/4 (with M5 female thread)
C01	Rc1/8
N01	NPT1/8 (with M5 female thread)
N02	NPT1/4 (with M5 female thread)
A2	URJ1/4 (Face seal fitting)
B2	TSJ1/4 (Compression fitting)

Output specifications

Nil	Voltage output type 1 to 5 V
28	Current output type 4 to 20 mA

Options/Part Nos.

Description	Part no.	Material	Note
Connector for pressure sensor controller	ZS-28-C	—	1 pc.
Adapter with restrictor Rc1/4	ZS-31-X175	Stainless steel 304	1 pc.
Adapter with restrictor NPT1/4	ZS-31-X186		1 pc.
Adapter with restrictor Rc1/8	ZS-31-X188		1 pc.
Adapter with restrictor NPT1/8	ZS-31-X189		1 pc.
Orifice M5	ZS-48-A	Stainless steel 303	1 pc.

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Specifications

Model	**PSE560** (Positive pressure)	**PSE561** (Vacuum)	**PSE563** (Compound pressure)	**PSE564** (Positive pressure)
Rated pressure range	0 to 1 MPa	0 to –101 kPa	–100 to 100 kPa	0 to 500 kPa
Extension analog output range	–0.1 to 0 MPa	10.1 to 0 kPa	—	–50 to 0 kPa
Proof pressure	1.5 MPa	500 kPa	500 kPa	750 kPa


Model		**PSE56□-□**	**PSE56□-□-28**
Applicable fluid		Liquid or gas that will not corrode or attack stainless steel 316L	
Power supply voltage		12 to 24 VDC ±10%, Ripple (p-p) 10% or less (with reverse connection protection)	
Current consumption		10 mA or less	—
Output specifications		Analog output: 1 to 5 V (within rated pressure range) 0.6 to 1 V (within extension analog output range) Output impedance: Approx. 1 kΩ	Analog output: 4 to 20 mA DC (within rated pressure range) Maximum load impedance: 500 Ω or less (at 24 VDC) 100 Ω or less (at 12 VDC)
Accuracy (Ambient temperature at 25°C)		±1% F.S. (within rated pressure range), ±3% F.S. (within extension analog output range)	
Linearity		±0.5% F.S.	
Repeatability		±0.2% F.S.	
Power supply voltage effect		±0.3% F.S.	
Environment	**Enclosure**	IP65	
	Operating temperature range	Operating: –10 to 60°C, Stored: –20 to 70°C (No freezing or condensation)	
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)	
	Withstand voltage	250 VAC for 1 min between terminals and housing	
	Insulation resistance	50 MΩ or more (50 VDC measured via megohmmeter) between terminals and housing	
Temperature characteristics		±2% F.S. (0 to 50°C: 25°C reference), ±3% F.S. (–10 to 60°C: 25°C reference)	
Sensor cable		PSE56□-□: Oilproof heavy-duty vinyl cable with air tubing, 3 cores, ø5.1, 3 m, Conductor area: 0.2 mm², Insulator O.D.: 1.12 mm PSE56□-□-28: Oilproof heavy-duty vinyl cable with air tubing, 2 cores, ø5.1, 3 m, Conductor area: 0.2 mm², Insulator O.D.: 1.12 mm	
Standards		CE/UKCA marking, UL/CSA (E216656)	

Piping Specifications


Part no.		**01**	**02**	**N01**	**N02**	**C01**	**A2**	**B2**
Port size		R1/8 M5 x 0.8	R1/4 M5 x 0.8	NPT1/8 M5 x 0.8	NPT1/4 M5 x 0.8	Rc1/8	URJ1/4	TSJ1/4
Material		Case: C3604 + Nickel plating, Piping port/Pressure sensor: Stainless steel 316L, Grease-free						
Weight	**With sensor cable**	193 g	200 g	194 g	201 g	187 g	203 g	193 g
	Without sensor cable	101 g	108 g	102 g	109 g	95 g	111 g	101 g

Internal Circuits and Wiring Examples

PSE56□-□
Voltage output type
1 to 5 V
Output impedance
Approx. 1 kΩ




PSE56□-□-28
Current output type
4 to 20 mA
Allowable load impedance
500 Ω or less (at 24 VDC)
100 Ω or less (at 12 VDC)




∗ Install the load either on the LINE (+) or LINE (–) side.

Analog Output

1 to 5 VDC




4 to 20 mA DC



Range	Rated pressure range	A	B	C
For vacuum	0 to –101 kPa	0	–101 kPa	10.1 kPa
For compound pressure	–100 kPa to 100 kPa	–100 kPa	100 kPa	—
For positive pressure	0 to 1 MPa	0	1 MPa	–0.1 MPa
	0 to 500 kPa	0	500 kPa	–50 kPa

Dimensions


PSE56□-$^{01}_{02}$, PSE56□-$^{N01}_{N02}$




∗ The dimensions of part C are common to all PSE56□ models.

Be sure to release the air in the air tubing of the cable to the atmosphere. If the air tubing is restricted, or left in environments where it is exposed to water or oil, it cannot be detected normally.


PSE56□-C01




PSE56□-B2




Adapter with restrictor
ZS-31-X□□□
Material:
Stainless steel 304



Orifice
ZS-48-A
Material:
Stainless steel 303



PSE56□-A2




[mm]

Model	A	B
PSE56□-01	8.2	R1/8
PSE56□-02	12	R1/4
PSE56□-N01	9.2	NPT1/8
PSE56□-N02	12.2	NPT1/4
PSE56□-C01	—	Rc1/8
PSE56□-A2	15.5	URJ1/4
PSE56□-B2	9.5	TSJ1/4

[mm]

Part no.	D	E	F	G	H	I
ZS-31-X188	20	9	R1/8	Rc1/8	14	1.5
ZS-31-X189	20	9	NPT1/8	NPT1/8	14	1.5
ZS-31-X175	29	13	R1/4	Rc1/4	17	1.6
ZS-31-X186	29	13	NPT1/4	NPT1/4	17	1.6

∗ If it is expected that the pressure, such as water hammer or surge pressure, will fluctuate rapidly, refer to the precautions in the Operation Manual on the SMC website, https://www.smcworld.com




Pressure Sensor/Switch for General Fluids

PSE570 Series

(Excludes the IO-Link/2-output type)

Series	Rated pressure range
	0 100 kPa 500 kPa 1 MPa 2 MPa 5 MPa 10 MPa
PSE570	0 – 1 MPa
PSE573	−100 kPa – 100 kPa
PSE574	0 – 500 kPa
PSE575	0 – 2 MPa
PSE576	0 – 5 MPa
PSE577	0 – 10 MPa

M12 connector



■ **Materials of Parts in Contact with Fluid**

	PSE570/573/574	PSE575/576/577
Piping port*1	C3604 + Nickel plating	
Pressure sensor*1	Al_2O_3 (Alumina 96%)	
Sensor seal	FKM + Grease	FKM


*1 Stainless steel 316L is used for the PSE560.
For details, refer to page 20.

Withstand voltage **500 VAC**
<Twice that of the PSE560>


IP65

Application examples


Liquid coolant pressure control



PET bottle molding machines



Liquid pressure control of gun drills



Applications

Pressure Sensor/Switch for General Fluids

PSE570 Series

Analog output type

IO-Link / 2-output type ▶ p. 25



How to Order

PSE57 0 – 01 – □ □

Sensor range

0	Positive pressure [0 to 1 MPa]
3	Compound pressure [–100 to 100 kPa]
4	Positive pressure [0 to 500 kPa]
5	Positive pressure [0 to 2 MPa]
6	Positive pressure [0 to 5 MPa]
7	Positive pressure [0 to 10 MPa]

Option (Lead wire)

Nil	Lead wire and M12 connector (3 m), Straight
L	Lead wire and M12 connector (3 m), Right angle
N	None

∗ See page 58 for connection to the PSE300AC.

Output specification

Nil	Voltage output type 1 to 5 V
28	Current output type 4 to 20 mA

Port size

Symbol	Port size	Model					
		PSE570	PSE573	PSE574	PSE575	PSE576	PSE577
01	R1/8 (with M5 female thread)	●	●	●	—	—	—
02	R1/4 (with M5 female thread)	●	●	●	●	●	●

Options/Part Nos.

	Description	Part no.	Material	Note
①	Lead wire and M12 connector (3 m), Straight	ZS-37-A	—	1 pc.
②	Lead wire and M12 connector (3 m), Right angle	ZS-37-B	—	1 pc.
③	Assembly-type connector	PCA-1557743	—	1 pc.
④	Adapter with restrictor Rc1/4	ZS-31-X175	Stainless steel 304	1 pc.
⑤	Adapter with restrictor Rc1/8	ZS-31-X188		1 pc.
⑥	Orifice M5	ZS-48-A	Stainless steel 303	1 pc.
⑦	① + ③	ZS-37-A-X448	—	The lead wire and connector are shipped together. (Not assembled)
⑧	② + ③	ZS-37-B-X449	—	
⑨	Connector for pressure sensor controller connection	ZS-28-CA-4	—	1 pc.

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Specifications

	Model	PSE570	PSE573	PSE574	PSE575	PSE576	PSE577
Fluid	**Applicable fluid**	Gas or liquid that will not corrode materials of parts in contact with fluid					
Pressure	**Rated pressure range**	0 to 1 MPa	–100 to 100 kPa	0 to 500 kPa	0 to 2 MPa	0 to 5 MPa	0 to 10 MPa
	Proof pressure	3.0 MPa	600 kPa	1.5 MPa	5.0 MPa	12.5 MPa	30 MPa
Electrical	**Power supply voltage**	12 to 24 VDC ±10% with 10% voltage ripple or less					
	Current consumption	10 mA or less					
	Protection	Reverse connection protection					
Accuracy	Analog output accuracy (Ambient temperature at 25°C)	±1.0% F.S.			±2.5% F.S.		
	Linearity	±0.5% F.S.					
	Repeatability (Ambient temperature at 25°C)	±0.2% F.S.			±0.5% F.S.		
	Temperature characteristics (25°C reference)	±2% F.S. (0 to 50°C) ±3% F.S. (–10 to 60°C)	±3% F.S. (0 to 50°C) ±4% F.S. (–10 to 60°C)		±5% F.S. (–10 to 60°C)		
Environment	**Enclosure**	IP65					
	Withstand voltage	500 VAC for 1 min between terminals and housing					
	Insulation resistance	100 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing					
	Operating temperature range	Operating: –10 to 60°C, Stored: –20 to 70°C (No freezing or condensation)					
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)					
Standards		CE/UKCA marking, UL/CSA (E216656)					
Materials of parts in contact with fluid		Piping port: C3604 + Nickel plating, Pressure sensor: Al_2O_3 (Alumina 96%), Sensor seal: FKM + Grease			Piping port: C3604 + Nickel plating, Pressure sensor: Al_2O_3 (Alumina 96%), Sensor seal: FKM		

	Model	PSE57□-□	PSE57□-□-28
Analog output	**Output**	Voltage output: 1 to 5 V	Current output: 4 to 20 mA
	Impedance	Output impedance: Approx. 1 kΩ	Maximum load impedance: 500 Ω or less (at 24 VDC) 100 Ω or less (at 12 VDC)

Pressure Sensor/Switch for General Fluids

PSE570 Series

IO-Link / 2-output type

Analog output type ▶ p. 24



How to Order

Output specification

L2	IO-Link/Switch: 1 output + 2 outputs (PNP or NPN switching type for switch output)

IO-Link PSE57 0 – 01 – L2 ☐

Switch output PSE57 0 – 01 – A ☐ – ☐ ❶

Sensor range

0	Positive pressure [0 to 1 MPa]
3	Compound pressure [–100 to 100 kPa]
4	Positive pressure [0 to 500 kPa]
5	Positive pressure [0 to 2 MPa]
6	Positive pressure [0 to 5 MPa]
7	Positive pressure [0 to 10 MPa]

Port size

Symbol	Port size	Model					
		PSE570	PSE573	PSE574	PSE575	PSE576	PSE577
01	R1/8 (with M5 female thread)	●	●	●	—	—	—
02	R1/4 (with M5 female thread)	●	●	●	●	●	●

Option (Lead wire)

Nil	Lead wire and M12 connector (3 m), Straight
L	Lead wire and M12 connector (3 m), Right angle
N	None

Output specification

A	NPN open collector 2 outputs
B	PNP open collector 2 outputs

❶ Set value (When output specification "N" or "P" is selected)

P 005 5 P 005 5 (Not filled in when "OF" is selected)

OUT1 output type

P	Normal output
N	Reversed output

OUT1 set value (P1/n1)

OUT1 hysteresis (H1)

OUT2 output type


P	Normal output
N	Reversed output
OF	Unused

OUT2 hysteresis (H2)

OUT2 set value (P2/n2)


Normal output

Switch output



Reversed output

Switch output



Options/Part Nos.

	Description	Part no.	Material	Note
①	Lead wire and M12 connector (3 m), Straight	ZS-37-A	—	1 pc.
②	Lead wire and M12 connector (3 m), Right angle	ZS-37-B	—	1 pc.
③	Assembly-type connector	PCA-1557743	—	1 pc.
④	Adapter with restrictor Rc1/4	ZS-31-X175	Stainless steel 304	1 pc.
⑤	Adapter with restrictor Rc1/8	ZS-31-X188		1 pc.
⑥	Orifice M5	ZS-48-A	Stainless steel 303	1 pc.
⑦	① + ③	ZS-37-A-X448	—	The lead wire and connector are shipped together. (Not assembled)
⑧	② + ③	ZS-37-B-X449	—	

	Description	Part no.	Material	Note
⑨	Lead wire and M12 connector (Connector on both sides)	EX9-AC005-SSPS	—	Length: 0.5 m, Straight
		EX9-AC010-SSPS	—	Length: 1 m, Straight
		EX9-AC020-SSPS	—	Length: 2 m, Straight
		EX9-AC030-SSPS	—	Length: 3 m, Straight
		EX9-AC050-SSPS	—	Length: 5 m, Straight
		EX9-AC100-SSPS	—	Length: 10 m, Straight
⑩	Connector for pressure sensor controller connection	ZS-28-CA-4	—	1 pc.

∗ The lead wire with an M12 connector is not included with the product. Please order it separately.

OUT1 Set Value (P1/n1)
OUT2 Set Value (P2/n2)

Symbol	Sensor range					
	PSE570	**PSE573**	**PSE574**	**PSE575**	**PSE576**	**PSE577**
-10		–100 kPa*1				
-09		–90 kPa				
-08		–80 kPa				
-07		–70 kPa				
-06		–60 kPa				
-05		–50 kPa				
-04		–40 kPa				
-03		–30 kPa				
-02		–20 kPa				
-01	–0.1 MPa*1	–10 kPa	–50 kPa*1			
000	0.0 MPa	0 kPa	0 kPa	0.0 MPa*1	0.0 MPa*1	0 MPa*1
001	0.1 MPa	10 kPa	50 kPa	0.2 MPa	0.5 MPa	1 MPa
002	0.2 MPa	20 kPa	100 kPa	0.4 MPa	1.0 MPa	2 MPa
003	0.3 MPa	30 kPa	150 kPa	0.6 MPa	1.5 MPa	3 MPa
004	0.4 MPa	40 kPa	200 kPa	0.8 MPa	2.0 MPa	4 MPa
005	0.5 MPa	50 kPa	250 kPa	1.0 MPa	2.5 MPa	5 MPa
006	0.6 MPa	60 kPa	300 kPa	1.2 MPa	3.0 MPa	6 MPa
007	0.7 MPa	70 kPa	350 kPa	1.4 MPa	3.5 MPa	7 MPa
008	0.8 MPa	80 kPa	400 kPa	1.6 MPa	4.0 MPa	8 MPa
009	0.9 MPa	90 kPa	450 kPa	1.8 MPa	4.5 MPa	9 MPa
010	1.0 MPa*1	100 kPa*1	500 kPa*1	2.0 MPa*1	5.0 MPa*1	10 MPa*1

OUT1 Hysteresis (H1)
OUT2 Hysteresis (H2)

Symbol	Sensor range					
	PSE570	**PSE573**	**PSE574**	**PSE575**	**PSE576**	**PSE577**
0	0.00 MPa	0 kPa	0 kPa	0.00 MPa	0.00 MPa	0.0 MPa
1	0.01 MPa	1 kPa	5 kPa	0.02 MPa	0.05 MPa	0.1 MPa
2	0.02 MPa	2 kPa	10 kPa	0.04 MPa	0.10 MPa	0.2 MPa
3	0.03 MPa	3 kPa	15 kPa	0.06 MPa	0.15 MPa	0.3 MPa
4	0.04 MPa	4 kPa	20 kPa	0.08 MPa	0.20 MPa	0.4 MPa
5	0.05 MPa	5 kPa	25 kPa	0.10 MPa	0.25 MPa	0.5 MPa
6	0.06 MPa	6 kPa	30 kPa	0.12 MPa	0.30 MPa	0.6 MPa
7	0.07 MPa	7 kPa	35 kPa	0.14 MPa	0.35 MPa	0.7 MPa
8	0.08 MPa	8 kPa	40 kPa	0.16 MPa	0.40 MPa	0.8 MPa
9	0.09 MPa	9 kPa	45 kPa	0.18 MPa	0.45 MPa	0.9 MPa
A	0.10 MPa	10 kPa	50 kPa	0.20 MPa	0.50 MPa	1.0 MPa

*1 Product number whose switch output switching point is out of set pressure range cannot be selected.
Normal output: P1 – H1 ≥ set pressure range low limit
When reverse output: n1 + H1 ≤ set pressure range high limit
Please confirm that it is.
*2 If you wish to use a set-up setting other than the above, contact your SMC sales representative

Ordering Examples

- **Pressure range: PSE576**
- **Port size: 02**
- **Output specification: PNP open collector 2 outputs**
- **Lead wire: Lead wire and M12 connector (3 m), Right angle**
- **OUT1: Normal output, Set point 2.5 MPa, Hysteresis 0.05 MPa**
- **OUT2: Unused**

PSE576-02-BL-P0051OF

Specifications

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

			IO-Link					
Model			PSE570-□-L2	PSE573-□-L2	PSE574-□-L2	PSE575-□-L2	PSE576-□-L2	PSE577-□-L2
Applicable fluid			Gas or liquid that will not corrode the materials of parts in contact with fluid					
Pressure	Rated pressure range		0.000 to 1.000 MPa	−100.0 to 100.0 kPa	0 to 500 kPa	0.000 to 2.000 MPa	0.00 to 5.00 MPa	0.00 to 10.00 MPa
	Set pressure range		−0.105 to 1.050 MPa	−105.0 to 105.0 kPa	−50 to 525 kPa	−0.105 to 2.100 MPa	−0.10 to 5.25 MPa	−0.10 to 10.50 MPa
	Smallest settable increment		0.001 MPa	0.1 kPa	1 kPa	0.001 MPa	0.01 MPa	0.01 MPa
	Proof pressure		3 MPa	600 kPa	1.5 MPa	5 MPa	12.5 MPa	30 MPa
Electrical	Power supply voltage	When used as a switch output device (When not used as an IO-Link device)	12 to 24 VDC ±10%, Ripple (p-p) 10% or less					
		When used as an IO-Link device	18 to 30 VDC, including ripple (p-p) 10%					
	Current consumption		35 mA or less					
	Protection		Reverse connection protection					
Switch output			NPN or PNP open collector 2 outputs (Selectable) Hysteresis, Window comparator, Error output Normal, Reversed Max. load current: 80 mA Max. applied voltage: 30 V Internal voltage drop (Residual voltage): 1.5 V or less (at load current of 80 mA) Delay time: 3.4 ms or less, Variable from 0 to 60 s/0.01 s increments					
Accuracy	Accuracy (Ambient temperature at 25°C)		±1.0% F.S.			±2.5% F.S.		
	Linearity		±0.5% F.S.					
	Repeatability (Ambient temperature at 25°C)		±0.2% F.S.			±0.5% F.S.		
	Temperature characteristics		±2% F.S. (0 to 50°C) ±3% F.S. (−10 to 60°C)	±3% F.S. (0 to 50°C) ±4% F.S. (−10 to 60°C)		±5% F.S. (−10 to 60°C)		
Environment	Enclosure		IP65					
	Withstand voltage		500 VAC for 1 min between terminals and housing					
	Insulation resistance		100 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing					
	Operating temperature range		Operating: −10 to 60°C, Stored: −20 to 70°C (No freezing or condensation)					
	Operating humidity range		Operating/Stored: 35 to 85% RH (No condensation)					
Standards			CE/UKCA marking, UL/CSA (E216656)					
Materials of parts in contact with fluid			Piping port: C3604 + Nickel plating, Pressure sensor: Al_2O_3 (Alumina 96%), Sensor seal: FKM + Grease			Piping port: C3604 + Nickel plating, Pressure sensor: Al_2O_3 (Alumina 96%), Sensor seal: FKM		

Communication	IO-Link type	Device
	IO-Link version	V1.1
	Communication speed	COM2 (38.4 kbps)
	Configuration file	IODD file
	Min. cycle time	3.4 ms
	Process data length	Input data: 4 bytes, Output data: 0 bytes
	On request data communication	Yes
	Data storage function	Yes
	Event function	Yes
	Vendor ID	131 (0 x 0083)
	Indicator light	SIO mode: Lights up when switch output is turned ON (OUT1: Green, OUT2: Red) IO-Link communication: Green light is ON or flashing. Error: Red light is flashing.

Specifications

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Model		Switch output					
		PSE570-□-A/B	**PSE573-□-A/B**	**PSE574-□-A/B**	**PSE575-□-A/B**	**PSE576-□-A/B**	**PSE577-□-A/B**
Applicable fluid		Gas or liquid that will not corrode the materials of parts in contact with fluid					
Pressure	**Rated pressure range**∗1	0.000 to 1.000 MPa	−100.0 to 100.0 kPa	0 to 500 kPa	0.000 to 2.000 MPa	0.00 to 5.00 MPa	0.00 to 10.00 MPa
	Set pressure range∗1	−0.105 to 1.050 MPa	−105.0 to 105.0 kPa	−50 to 525 kPa	−0.105 to 2.100 MPa	−0.10 to 5.25 MPa	−0.10 to 10.50 MPa
	Smallest settable increment∗1	0.001 MPa	0.1 kPa	1 kPa	0.001 MPa	0.01 MPa	0.01 MPa
	Proof pressure	3 MPa	600 kPa	1.5 MPa	5 MPa	12.5 MPa	30 MPa
Electrical	**Power supply voltage**	12 to 24 VDC ±10%, Ripple (p-p) 10% or less					
	Current consumption	35 mA or less					
	Protection	Reverse connection protection					
Switch output		NPN or PNP open collector 2 outputs Hysteresis Normal, Reversed Max. load current: 80 mA Max. applied voltage: 30 V Internal voltage drop (Residual voltage): 1.5 V or less (at load current of 80 mA) Delay time: 3.4 ms or less					
Accuracy	**Accuracy (Ambient temperature at 25°C)**	±1.0% F.S.			±2.5% F.S.		
	Linearity	±0.5% F.S.					
	Repeatability (Ambient temperature at 25°C)	±0.2% F.S.			±0.5% F.S.		
	Temperature characteristics	±2% F.S. (0 to 50°C) ±3% F.S. (−10 to 60°C)	±3% F.S. (0 to 50°C) ±4% F.S. (−10 to 60°C)		±5% F.S. (−10 to 60°C)		
Environment	**Enclosure**	IP65					
	Withstand voltage	500 VAC for 1 min between terminals and housing					
	Insulation resistance	100 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing					
	Operating temperature range	Operating: −10 to 60°C, Stored: −20 to 70°C (No freezing or condensation)					
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)					
Standards		CE/UKCA marking, UL/CSA (E216656)					
Materials of parts in contact with fluid		Piping port: C3604 + Nickel plating, Pressure sensor: Al_2O_3 (Alumina 96%), Sensor seal: FKM + Grease			Piping port: C3604 + Nickel plating, Pressure sensor: Al_2O_3 (Alumina 96%), Sensor seal: FKM		

∗1 Should you require settings other than those specified by the model indication method, please contact our sales representative.

Piping Specifications

Part no.		PSE570/573/574-01	PSE570/573/574-02	PSE575/576/577-02
Port size		R1/8 M5 x 0.8	R1/4 M5 x 0.8	R1/4 M5 x 0.8
Materials of parts in contact with fluid		Piping port: C3604 + Nickel plating Pressure sensor: Al_2O_3 (Alumina 96%) Sensor seal: FKM + Grease		Piping port: C3604 + Nickel plating Pressure sensor: Al_2O_3 (Alumina 96%) Sensor seal: FKM
Weight	**Without lead wire and M12 connector**	88 g	95 g	103 g
	With lead wire and M12 connector	175 g	182 g	191 g


Cable Specifications

Conductor	Nominal cross section	AWG23
	Outside diameter	0.72 mm
Insulator	**Material**	Cross-linked vinyl chloride
	Outside diameter	1.14 mm
	Color	Brown, Blue, Black, White
Sheath	**Material**	Oil resistant vinyl chloride
Finished O.D.		ø4
Length		3 m

Internal Circuits and Wiring Examples


PSE57□-□

Voltage output type
1 to 5 V
Output impedance
Approx. 1 kΩ



PSE57□-□-28


Current output type
4 to 20 mA
Allowable load impedance
500 Ω or less (at 24 VDC)
100 Ω or less (at 12 VDC)



*1 For the analog output type, the unconnected terminals are used in SMC, so please do not connect them.


PSE57□-□-A

NPN open collector (2 outputs)



PSE57□-□-B

PNP open collector (2 outputs)




PSE57□-□-L2


When used as a switch output device

* The numbers in the circuit diagrams show the connector pin layout.


Setting of NPN open collector 2 outputs



Setting of PNP open collector 2 outputs




When used as an IO-Link device




Analog Output

1 to 5 VDC




4 to 20 mA DC




Model	Rated pressure range	A	B
PSE570	0 to 1 MPa	0 MPa	1 MPa
PSE573	−100 to 100 kPa	−100 kPa	100 kPa
PSE574	0 to 500 kPa	0 kPa	500 kPa
PSE575	0 to 2 MPa	0 MPa	2 MPa
PSE576	0 to 5 MPa	0 MPa	5 MPa
PSE577	0 to 10 MPa	0 MPa	10 MPa

IO-Link: Process Data


PSE570-L2 (For positive pressure)




PSE573-L2 (For compound pressure)




PSE574-L2 (For positive pressure)




PSE575-L2 (For positive pressure)



PSE576-L2 (For positive pressure)



PSE577-L2 (For positive pressure)




Lead wire and M12 connector (Connector on both sides)


EX9-AC 005 -SSPS (With connector on both sides (Socket/Plug))


Cable length (L)

005	500 mm
010	1000 mm
020	2000 mm
030	3000 mm
050	5000 mm
100	10000 mm




Socket connector pin arrangement
A-coded (Normal key)






Plug connector pin arrangement
A-coded (Normal key)



Connections

Item	Specifications
Cable O.D.	ø6 mm
Conductor nominal cross section	0.3 mm²/AWG22
Wire O.D. (Including conductor)	1.5 mm
Min. bending radius (Fixed)	40 mm

Dimensions




*1 IO-Link/switch output specification only

[mm]


Part no.	A	B	C
PSE570/573/574-01	8	R1/8	36.5
PSE570/573/574-02	12	R1/4	36.5
PSE575/576/577-02	12	R1/4	39.7

Lead wire and M12 connector

ZS-37-A



ZS-37-B



Pin no.	Lead wire color	Description
1	Brown	DC (+)
2	White	N.C.*1/OUT2
3	Blue	DC (–)
4	Black	OUT1


*1 For the analog output type, the unconnected terminals are used in SMC, so please do not connect them.

Part no.	Description
ZS-37-A	Straight type 3 m
ZS-37-B	Right angle type 3 m

Adapter with restrictor

ZS-31-X□□□

Material:
Stainless steel 304




[mm]

Part no.	D	E	F	G	H	I
ZS-31-X188	20	9	R1/8	Rc1/8	14	1.5
ZS-31-X175	29	13	R1/4	Rc1/4	17	1.6

Orifice

ZS-48-A

Material:
Stainless steel 303



* If it is expected that the pressure, such as water hammer or surge pressure, will fluctuate rapidly, refer to the precautions in the Operation Manual on the SMC website, https://www.smcworld.com



3-Screen Display


Multi-channel Digital Sensor Monitor


PSE200A Series

CE UKCA RoHS IO-Link

Applicable sensors					Rated pressure range	Set/Display resolution
PSE53□	PSE54□	PSE55□	PSE56□	PSE57□		
PSE531	**PSE541**	—	**PSE561**	—	−101 kPa to 0	**0.1 kPa**
PSE533	**PSE543**	—	**PSE563**	**PSE573**	−100 kPa to 100 kPa	**0.1 kPa**
PSE530	**PSE540**	—	**PSE560**	**PSE570**	0 to 1 MPa	**0.001 MPa**
—	—	—	—	**PSE575**	0 to 2 MPa	**0.001 MPa**
—	—	—	—	**PSE576**	0 to 5 MPa	**0.01 MPa**
—	—	—	—	**PSE577**	0 to 10 MPa	**0.01 MPa**
PSE532	—	—	—	—	0 to 100 kPa	**0.1 kPa**
—	—	—	**PSE564**	**PSE574**	0 to 500 kPa	**1 kPa**
—	—	**PSE550**	—	—	0 to 2 kPa	**0.001 kPa**

Up to 4 pressure sensors can be connected!





It is possible to change the settings while checking the measured value.

Main screen — Measured value (Current pressure value)

Sub screen — Left side: Label (Display item); Right side: Set value (Threshold value)

Visualization of Settings

Set value (Threshold value)	P_1
Hysteresis value	H_1
Peak value	H_H1
Bottom value	H_Lo
Channel display	CH_1

- **Differential Pressure Check Mode** p. 34
- **Input Range Selection** p. 35
- **3 channels are displayed simultaneously.** p. 34

IO-Link Compatible

- **Hub Function**
  Convert analog signals to digital signals!
  ∗ For details, refer to the "Operation Manual" on the SMC website.




Applicable Pressure Sensor Variations


Compact Pneumatic Pressure Sensor PSE53□	Compact Pneumatic Pressure Sensor PSE54□	Low Differential Pressure Sensor PSE550	Pressure Sensor for General Fluids PSE56□	Pressure Sensor for General Fluids PSE57□
				

Visualization of Settings

Item and set value are displayed together.
Easy to confirm the displayed item




Mode Examples




Easy Screen Switching

It is possible to change the settings while checking the measured value.



The sub screen can be switched by pressing the down buttons.




∗ One additional arbitrary display mode can be added via the function settings.

CH display | Other channel | Customer defined label | Level bar

Simple 3-Step Setting

After selecting the channel, when the SET button is pressed and the set value (P_1) is displayed, the set value (threshold value) can be set.


When the SET button is pressed and the hysteresis (H_1) is being displayed, the hysteresis value can be set.



Now with a snap shot function for set value reading


Snap shot function


Pressing the ▲ and ▼ buttons simultaneously for a minimum of 1 second will make the set value (threshold value) the same as the current pressure value.



Centralized Control Saves Installation Space.

66% reduction in installation space
(Compared with the panel mounted Z/ISE20□)






Differential Pressure Check Mode


＊ For details, refer to the "Operation Manual" on the SMC website.

One monitor displays 2 lines of differential pressure.




A Single Monitor Various Applications

3 channels are displayed simultaneously.
(Customer defined channel can be set.)



Input Range Selection (for Pressure/Flow rate)



The sensor input range can be set to the required value and displayed. (Voltage input: 1 to 5 V)
Pressure switch/Flow switch can be displayed.

A is displayed for 1 V. B is displayed for 5 V.
The range can be set as required.
Refer to page 38 for the specification of the sensors which can be connected.
For the individual specifications of each connectable sensor, refer to the **Web Catalog**.

■ For Digital Flow Switch for Water / PF3W511



	A	B
PF3W504	0	4
PF3W520	0	16
PF3W540	0	40
PF3W511	0	100

Set A and B to the values shown in the table on the left.

■ For Flow Sensor / PFMV5




Setting of the display for analog voltage

	A	B
PFMV5 Series	1.00	5.00

Set A and B to the values shown in the table on the left.

Connectors

Connection and removal of wiring is easy.



Functions * For details, refer to the "Operation Manual" on the SMC website.

■ Auto-preset function
This function, when selected in the initial setting, calculates and stores the set value from the measured pressure.

■ Display value fine adjustment function
Fine adjustment of the indicated value of the pressure sensor can be made within the range of ±5% of the read value.

■ Peak/Bottom value indication function
This function constantly detects and updates the maximum (minimum) pressure when the power is supplied, and allows to hold the maximum (minimum) pressure value.

■ Key-lock function
This function prevents operation errors such as accidentally changing setting values.

■ Zero-clear function
This function clears and resets the zero value on the display of measured pressure.

■ Error display function
This function displays error location and content when a problem or error has occurred.

■ Anti-chattering function
This function prevents the detection of such temporary drops in the supply pressure as errors by changing the delay time setting.

■ Pressure range/Unit selection function
The pressure range and displayed unit can be switched.

■ Zero-cut setting
When the pressure display value is close to zero, this function forces the display to zero.

■ Selection of power-saving mode
Power-saving mode can be selected.
It shifts to power-saving mode automatically when there is no button operation for 30 seconds.

■ Setting of security code
Users can select whether a security code must be entered to release the key lock.

■ Auto-shift function
This function compensates for such supply pressure fluctuations. It measures the pressure at the time of auto-shift signal input and uses it as the reference pressure to correct the set value on the switch.

■ Differential pressure check mode
Set and display the differential pressure between CH1 - CH2, and CH3 - CH4.

■ Channel to channel copy function
The set values can be copied to other channel.

■ Channel select function
Pressure value for the selected channel is displayed.

■ Channel scan function
Pressure values for each channel are displayed in turn every 2 seconds.

Series Variations

		Digital Sensor Monitors		
		PSE200A	**PSE300AC** p. 54	**PSE300A** p. 44
				
Basic Specifications	Repeatability	**±0.1% (F.S.)**	±0.1% (F.S.)	
	Voltage	**12 to 24 VDC**	12 to 24 VDC	
	No. of outputs for switch	**5 outputs**	2 outputs	
	Analog output	—	—	1 to 5 V 4 to 20 mA
	Operating temperature	**0 to 50°C**	0 to 50°C	
Functions	Number of screens	**3**	3	
	Enclosure	**Front face: IP65** **Others: IP40**	IP65	IP40
	3 Step	**Yes**	Yes	
	Wiring	**Connector**	Connector	

Applicable Pressure Sensors

Compact Pneumatic Pressure Sensor **PSE53□**	Compact Pneumatic Pressure Sensor **PSE54□**	Low Differential Pressure Sensor **PSE550**	Pressure Sensor for General Fluids **PSE56□**	Pressure Sensor for General Fluids **PSE57□**
				
Rated pressure range	Rated pressure range	Rated pressure range	Rated pressure range	Rated pressure range
−101 kPa to 0 −100 kPa to 100 kPa 0 to 100 kPa 0 to 1 MPa	−101 kPa to 0 −100 kPa to 100 kPa 0 to 1 MPa	0 to 2 kPa	−101 kPa to 0 −100 kPa to 100 kPa 0 to 500 kPa 0 to 1 MPa	−100 kPa to 100 kPa 0 to 500 kPa 0 to 1 MPa 0 to 2 MPa 0 to 5 MPa 0 to 10 MPa

CONTENTS

How to Order ····· p. 37
Options/Part Nos. ····· p. 37
Specifications ····· p. 38
Applicable Pressure Sensors ····· p. 39
Internal Circuits and Wiring Examples ····· p. 39
Dimensions ····· p. 42

3-Screen Display
Multi-channel Digital Sensor Monitor
PSE200A Series



How to Order

PSE20 0 A – M □ □ □

Input/Output specification



0	NPN 5 outputs + Auto-shift input
1	PNP 5 outputs + Auto-shift input
2	IO-Link + NPN 4 outputs or NPN 5 outputs (SIO mode)
3	IO-Link + PNP 4 outputs or PNP 5 outputs (SIO mode)

Unit specification

Nil	With unit selection function*1
M	SI units only*2


*1 Under the New Measurement Act, switches with the unit selection function are no longer allowed for use in Japan.
*2 Fixed unit: kPa, MPa, Pa

Option 1

Nil	None
A	Panel mount adapter **ZS-26-B** 
B	Front protection cover + Panel mount adapter **ZS-26-C** 


* Options are not assembled, but shipped together.

Option 2

Nil	None
4C	Sensor connector (4 pcs.) **ZS-28-C** 

* Connector is not connected, but shipped together.
* This connector cannot be used with the PSE570 series.



Option 3

Nil	Power supply/Output connection cable (2 m) 
N	None

* Cable is shipped together, but not connected.

Options/Part Nos.

When only optional parts are required, order with the part numbers listed below.

Description	Part no.	Note
Panel mount adapter	**ZS-26-B**	Waterproof seal, Tapping screw: Nominal size 3 x 8 L (2 pcs.) included
Front protection cover + Panel mount adapter	**ZS-26-C**	Waterproof seal, Tapping screw: Nominal size 3 x 8 L (2 pcs.) included
□48 conversion adapter * This adapter is used to mount the PSE200A series on the panel fitting of the PSE100 series.	**ZS-26-D**  Order panel mount adapter separately.	
Front protection cover	**ZS-26-01**	
Sensor connector (1 pc. per set)	ZS-28-C	For the PSE5□□ series (Excludes the PSE570 series)
	ZS-28-CA-4	For PSE570 series
Power supply with M12 connector/Output cable (Made to Order) * For use when using an M12 connector for IO-Link communication	ZS-26-LM12 	

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Specifications

Series		PSE200A								
Applicable SMC pressure sensor		PSE550	PSE531 PSE541 PSE561	PSE533 PSE543 PSE563 PSE573	PSE532	PSE564 PSE574	PSE530 PSE540 PSE560 PSE570	PSE575	PSE576	PSE577
Rated pressure range		0 to 2 kPa	0 to −101 kPa	−100 to 100 kPa	0 to 100 kPa	0 to 500 kPa	0 to 1 MPa	0 to 2 MPa	0 to 5 MPa	0 to 10 MPa
Display/Set pressure range		−0.2 to 2.1 kPa	10 to −105 kPa	−105 to 105 kPa	−10 to 105 kPa	−50 to 525 kPa	−0.105 to 1.05 MPa	−0.105 to 2.1 MPa	−0.25 to 5.25 MPa	−0.5 to 10.5 MPa
Display/Smallest settable increment		0.001 kPa	0.1 kPa	0.1 kPa	0.1 kPa	1 kPa	0.001 MPa	0.001 MPa	0.01 MPa	0.01 MPa
Electrical	Power supply voltage: **When used as a switch output device**	12 to 24 VDC ±10% with 10% ripple (p-p) or less								
	Power supply voltage: **When used as an IO-Link device**	18 to 30 VDC, including ripple (p-p) 10%*1								
	Current consumption	55 mA or less								
	Protection	Polarity protection								
	Power supply voltage for sensor*1	[Power supply voltage] −1.5 V								
	Power supply current for sensor*2	Max. 50 mA (However, the total current for the 4 inputs is 200 mA maximum or less.)								
Accuracy	**Display accuracy**	±0.5% F.S. ±1 digit (Ambient temperature of 25 ±3°C)								
	Repeatability	±0.1% F.S. ±1 digit								
	Temperature characteristics	±0.5% F.S. (Reference: 25°C)								
Switch output (SIO mode)	**Output type**	NPN or PNP open collector output: 5 outputs								
	Output mode	Hysteresis mode, Window comparator mode, Error output, Output OFF								
	Switch operation	Normal output, Reversed output								
	Max. load current	80 mA								
	Max. applied voltage (NPN only)	30 VDC								
	Internal voltage drop (Residual voltage)	1.5 V or less (at load current of 80 mA)								
	Delay time*3	5 ms or less, variable from 0 to 60 s/0.01 s increments								
	Hysteresis	Variable from 0*4								
	Protection	Over current protection								
Sensor input	**Input type**	Voltage input: 1 to 5 VDC (Input impedance: 1 MΩ)								
	Number of inputs	4 inputs								
	Connection method	e-CON								
	Protection	Over voltage protection (up to a voltage of 26.4 VDC)								
Auto-shift input*5		Voltage free input (Reed or Solid state), input for 5 ms or longer, Independently controllable auto-shift function ON/OFF								
Display	**Unit***6	MPa, kPa, Pa, kgf/cm², bar, mbar, psi, inHg, mmHg, mmH₂O (depends on selected range)								
	Display type	LCD								
	Number of screens	3-screen display (Main screen, Sub screen x 2)								
	Display color	Main screen: Red/Green, Sub screen: Orange								
	Number of display digits	Main screen: 4 digits (7 segments), Sub screen (Left): 4 digits (some digits are 11-segments, 7 segments for other), Sub screen (Right): 5 digits (some digits are 11-segments, 7 segments for other)								
	Indicator light	Lights up when switch output is turned ON. OUT1, OUT2: Orange								
Digital filter*7		Variable from 0 to 30 s/0.01 s increments								
Environment	**Enclosure**	Front face: IP65 (when panel-mounted), Others: IP40*8								
	Withstand voltage	1000 VAC for 1 min between terminals and housing								
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing								
	Operating temperature range	Operating: 0 to 50°C, Stored: −10 to 60°C (No condensation)								
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)								
Standards		CE/UKCA marking								
Weight	**Body**	51 g (Excludes power supply and output cable)								
	Power supply/Output cable	60 g								
	e-CON (1 pc.)	2 g								
Communication (IO-Link mode)	**IO-Link type**	Device								
	IO-Link version	V1.1								
	Communication speed	COM2 (38.4 kbps)								
	Configuration file	IODD file*9								
	Minimum cycle time	4.8 ms								
	Process data length	Input data: 10 bytes, Output data: 0 bytes								
	On request data communication	Yes								
	Data storage function	Yes								
	Event function	Yes								
	Vendor ID	131 (0 x 0083)								

*1 Check the power supply voltage range of the connected sensor.
*2 Over current on DC (+) side and DC (−) side of the sensor input connector results in breakage of the product.
*3 Value without digital filter (at 0 ms)
*4 If the applied pressure fluctuates around the set value, the hysteresis must be set to a value more than the amount of fluctuation, or chattering will occur.
*5 This setting is only possible for the PSE200A/PSE201A.
*6 This setting is only possible for models with the unit selection function. Only MPa, kPa, or Pa is available for models without this function.
*7 The response time indicates when the set value is 90% in relation to the step input.
*8 If □48 conversion adapter is used, it meets IP40.
*9 The configuration file can be downloaded from the SMC website, https://www.smcworld.com
* Products with tiny scratches, marks, or display color or brightness variations which do not affect the performance of the product are verified as conforming products.

Cable Specifications

Conductor area		0.15 mm² (AWG26)
Insulator	**O.D.**	0.9 mm
Sheath	**Finished O.D.**	ø4.8

Applicable Pressure Sensors

Applicable SMC pressure sensor					Rated pressure range
PSE53□	PSE54□	PSE550	PSE56□	PSE57□	−100 kPa 0 100 kPa 500 kPa 1 MPa 2 MPa 5 MPa 10 MPa
PSE531	PSE541	—	PSE561	—	−101 kPa 0
PSE533	PSE543	—	PSE563	PSE573	−100 kPa 100 kPa
PSE532	—	—	—	—	0 100 kPa
—	—	—	PSE564	PSE574	0 500 kPa
PSE530	PSE540	—	PSE560	PSE570	0 1 MPa
—	—	—	—	PSE575	0 2 MPa
—	—	—	—	PSE576	0 5 MPa
—	—	—	—	PSE577	0 10 MPa
—	—	PSE550	—	—	0 2 kPa


Internal Circuits and Wiring Examples

PSE20□A−□□□□

Input/Output specifications


0

· NPN open collector 5 outputs + Auto-shift 1 input



1

· PNP open collector 5 outputs + Auto-shift 1 input



Internal Circuits and Wiring Examples


PSE20□A−□□□□

Input/Output specifications


2

· IO-Link/NPN open collector 1 output + NPN open collector 4 outputs

When used as an IO-Link device



When used as a switch output device



Internal Circuits and Wiring Examples


PSE20□A−□□□□

Input/Output specifications


3

· IO-Link/PNP open collector 1 output + PNP open collector 4 outputs


When used as an IO-Link device




When used as a switch output device



Dimensions






Sensor connector (4P x 4)

Pin no.	Terminal
①	DC (+)
②	N.C
③	DC (–)
④	IN (1 to 5 V)


Connector (Option)



Power supply/Output connector (8P)


Pin no.	Terminal	
	PSE200A/PSE201A	PSE202A/PSE203A
①	DC (+)	L+
②	DC (–)	L–
③	CH1_OUT1	C/Q (CH1_OUT1)
④	CH1_OUT2	
⑤	CH2_OUT1	
⑥	CH3_OUT1	
⑦	CH4_OUT1	
⑧	Auto-shift input	N.C.

Power supply/Output connection cable (Accessory)





Power supply with M12 connector/Output cable (Made to Order)


∗ For use when using an M12 connector for IO-Link communication



Front protection cover + Panel mount adapter









Panel fitting dimensions
Applicable panel thickness:
0.5 to 8 mm

□48 conversion adapter + Panel mount adapter







3-Screen Display

Sensor Monitor

PSE300A Series

Applicable sensors					Rated pressure range	Set/Display resolution
PSE53□	PSE54□	PSE55□	PSE56□	PSE57□	−100 kPa 0 100 kPa 500 kPa 1 MPa 10 MPa	
PSE531	**PSE541**	—	**PSE561**	—	−101 kPa to 0	**0.1 kPa**
PSE533	**PSE543**	—	**PSE563**	**PSE573**	−100 kPa to 100 kPa	**0.1 kPa**
PSE530	**PSE540**	—	**PSE560**	**PSE570**	0 to 1 MPa	**0.001 MPa**
—	—	—	—	**PSE575**	0 to 2 MPa	**0.001 MPa**
—	—	—	—	**PSE576**	0 to 5 MPa	**0.01 MPa**
—	—	—	—	**PSE577**	0 to 10 MPa	**0.01 MPa**
PSE532	—	—	—	—	0 to 100 kPa	**0.1 kPa**
—	—	—	**PSE564**	**PSE574**	0 to 500 kPa	**1 kPa**
—	—	**PSE550**	—	—	0 to 2 kPa	**0.001 kPa**



Compact Pneumatic Pressure Sensor **PSE54□**



Low Differential Pressure Sensor **PSE550**



Pressure Sensor for General Fluids **PSE57□**



Compact Pneumatic Pressure Sensor **PSE53□**

Compatible with 5 types of pressure sensor





Pressure Sensor for General Fluids **PSE56□**

It is possible to change the settings while checking the measured value.



Main screen
Measured value
(Current pressure value)

Sub screen

Left side	Right side
Label (Display item)	Set value (Threshold value)

Visualization of Settings

Set value (Threshold value)	P_1	Hysteresis value	H_1
Peak value	H_H1	Bottom value	H_Lo

NPN/PNP Switch Function



Selectable

NPN **PNP**

1 sensor monitor for 2 output types reduces stock.

Input Range Selection (for Pressure/Flow rate)

- **Set the displayed value according to the sensor input.** (Voltage input: 1 to 5 V/Current input: 4 to 20 mA)
- **Value is displayed regardless of the pressure switch or flow switch.**






Improved Operability


Visualization of Settings


The sub screen (label) shows the item to be set.



Simple 3-Step Setting


When the S button is pressed and the set value (P_1) is being displayed, the set value (threshold value) can be set.
When the S button is pressed and the hysteresis (H_1) is being displayed, the hysteresis value can be set.






Easy Screen Switching

It is possible to change the settings while checking the measured value.




The sub screen can be switched by pressing the up/down buttons.




∗ One additional arbitrary display mode can be added via the function settings.

Copy Function

The set values of the sensor can be copied.




Easy Fitting of Connector




Input Range Selection (for Pressure/Flow rate)


The displayed value to the sensor input can be set as required.
(Voltage input: 1 to 5 V/Current input: 4 to 20 mA)
Pressure switch/Flow switch can be displayed.

A is displayed for 1 V (or 4 mA).
B is displayed for 5 V (or 20 mA).
The range can be set as required.



■ For Digital Flow Switch for Water/PF3W511






	A	B
PF3W504	0	4
PF3W520	0	16
PF3W540	0	40
PF3W511	0	100

Set A and B to the values shown in the table on the left.


Analog Free Span Function

For the displayed value, the analog span point (5 V, 20 mA) can be changed within the rated pressure range of 10 to 105%*1.




*1 Up to the upper limit of the display/set pressure range.

[Application example]
To output 5 V from the pressure controller at 0.75 MPa, using a sensor that outputs 1 to 5 V at 0 to 1 MPa.



Application Example

Centralized control of distributed pressure switches is possible.



Series Variations

Digital Sensor Monitors

		PSE300A	PSE200A p. 32	PSE300AC p. 54
				
Basic Specifications	Repeatability	±0.1% (F.S.)	±0.1% (F.S.)	
	Voltage	12 to 24 VDC	12 to 24 VDC	
	No. of outputs for switch	2 outputs	5 outputs	2 outputs
	Analog output	1 to 5 V 4 to 20 mA	—	
	Operating temperature	0 to 50°C	0 to 50°C	
Functions	Number of screens	3	3	
	Enclosure	IP40	Front face: IP65 Others: IP40	IP65
	3-step setting	Yes	Yes	
	Wiring	Connector	Connector	

Applicable Pressure Sensors

Compact Pneumatic Pressure Sensor **PSE53□**	Compact Pneumatic Pressure Sensor **PSE54□**	Low Differential Pressure Sensor **PSE550**	Pressure Sensor for General Fluids **PSE56□**	Pressure Sensor for General Fluids **PSE57□**
				
Rated pressure range	**Rated pressure range**	**Rated pressure range**	**Rated pressure range**	**Rated pressure range**
−101 kPa to 0 −100 kPa to 100 kPa 0 to 100 kPa 0 to 1 MPa	−101 kPa to 0 −100 kPa to 100 kPa 0 to 1 MPa	0 to 2 kPa	−101 kPa to 0 −100 kPa to 100 kPa 0 to 500 kPa 0 to 1 MPa	−100 kPa to 100 kPa 0 to 500 kPa 0 to 1 MPa 0 to 2 MPa 0 to 5 MPa 0 to 10 MPa

CONTENTS

How to Order ····· p. 48
Options/Part Nos. ····· p. 48
Specifications ····· p. 49
Internal Circuits and Wiring Examples ····· p. 50
Dimensions ····· p. 51

3-Screen Display Sensor Monitor
PSE300A Series



How to Order

PSE3 0 0 A – M □ □ □

❶ ❷ ❸ ❹ ❺ ❻

❶ Input specification

Symbol	Description
0	Voltage input
1	Current input

❷ Output specification

Symbol	Description	Factory default settings
0	NPN/PNP open collector 2 outputs switching type + Analog voltage/Auto-shift/Copy function switching type	NPN open collector 2 outputs + Analog voltage*1
3		PNP open collector 2 outputs + Analog voltage*1
1	NPN/PNP open collector 2 outputs switching type + Analog current/Auto-shift/Copy function switching type	NPN open collector 2 outputs + Analog current*2
4		PNP open collector 2 outputs + Analog current*2
6	NPN/PNP open collector 2 outputs switching type + Copy function	NPN open collector 2 outputs + Copy function


∗1, 2 Although the default output specifications differ, the output specifications are the same.

❸ Unit specification




Symbol	Description
Nil	With unit selection function*1
M	SI units only*2

∗1 Under the New Measurement Act, switches with the unit selection function are no longer allowed for use in Japan.
∗2 Fixed unit: MPa, kPa, Pa


❹ Option 1

Symbol	Description	
Nil	Without lead wire	
L	Lead wire with connector (2 m lead wire)	ZS-46-5L  Power supply/output lead wire with connector

❺ Option 2

Symbol	Description	
Nil	None	
A	Bracket	ZS-46-A1 
B	Panel mount adapter	ZS-46-B  Panel; Panel mount adapter
D	Panel mount adapter + Front protection cover	ZS-46-D  Panel; Front protection cover; Panel mount adapter

❻ Option 3

Symbol	Description	
Nil	None	
C	Sensor connector	ZS-28-C  Sensor connector

∗ This connector cannot be used with the PSE570 series.

Options/Part Nos.

When only optional parts are required, order with the part numbers listed below.

Description	Part no.	Note
Bracket	**ZS-46-A1**	—
Panel mount adapter	**ZS-46-B**	—
Panel mount adapter + Front protection cover	**ZS-46-D**	—
Lead wire with connector	**ZS-46-5L**	5-core, 2 m
Front protection cover	**ZS-27-01**	—
Sensor connector (1 pc. per set)	**ZS-28-C**	For the PSE5□□ series (Excludes the PSE570 series)
	ZS-28-CA-4	For the PSE570 series

Specifications

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Series			PSE300A								
Applicable SMC pressure sensor			PSE550	PSE531 PSE541 PSE561	PSE533 PSE543 PSE563 PSE573	PSE532	PSE564 PSE574	PSE530 PSE540 PSE560 PSE570	PSE575	PSE576	PSE577
Rated pressure range			0 to 2 kPa	0 to −101 kPa	−100 to 100 kPa	0 to 100 kPa	0 to 500 kPa	0 to 1 MPa	0 to 2 MPa	0 to 5 MPa	0 to 10 MPa
Display/Set pressure range			−0.2 to 2.1 kPa	10 to −105 kPa	−105 to 105 kPa	−10 to 105 kPa	−50 to 525 kPa	−0.105 to 1.05 MPa	−0.105 to 2.1 MPa	−0.25 to 5.25 MPa	−0.50 to 10.5 MPa
Display/Smallest settable increment			0.001 kPa	0.1 kPa	0.1 kPa	0.1 kPa	1 kPa	0.001 MPa	0.001 MPa	0.01 MPa	0.01 MPa
Electrical	Power supply voltage		12 to 24 VDC ±10%, Ripple (p-p) 10% or less								
	Current consumption		35 mA or less								
	Protection		Polarity protection								
Accuracy	Display accuracy		±0.5% F.S. ±1 digit (Ambient temperature of 25°C)								
	Repeatability		±0.1% F.S. ±1 digit								
	Analog output accuracy (To display value)		±0.5% F.S.								
	Analog output linearity		±0.2% F.S.								
	Temperature characteristics		±0.5% F.S. (Reference: 25°C)								
Switch output	Output type		Select from NPN or PNP open collector 2 outputs.								
	Output mode		Select from Hysteresis, Window comparator, Error output, or Switch output OFF modes.								
	Switch operation		Select from Normal or Reversed output.								
	Max. load current		80 mA								
	Max. applied voltage (NPN only)		30 VDC								
	Internal voltage drop (Residual voltage)		NPN: 1 V or less (at load current of 80 mA) PNP: 1.5 V or less (at load current of 80 mA)								
	Delay time*1		1.5 ms or less (with anti-chattering function: 20, 100, 500, 1000, 2000, 5000 ms)								
	Hysteresis	Hysteresis mode Window comparator mode	Variable from 0*2								
	Protection		Over current protection								
Analog output	Voltage output	Output type*3	Voltage output: 1 to 5 V Extension analog output range: 0.6 to 1 V								
		Output impedance	Approx. 1 kΩ								
	Current output	Output type*3	Current output: 4 to 20 mA Extension analog output range: 2.4 to 4 mA								
		Load impedance	Maximum load impedance at power supply voltage of 12 V: 300 Ω at power supply voltage of 24 V: 600 Ω Minimum load impedance: 50 Ω								
	Analog response time		50 ms or less								
Auto-shift input	Input type		Non-voltage input: 0.4 V or less								
	Input mode		Select from Auto-shift or Auto-shift zero.								
	Input time		5 ms or more								
Sensor input	Input type		PSE30□A: Voltage input 1 to 5 VDC (Input impedance: 1 MΩ) PSE31□A: Current input 4 to 20 mA DC (Input impedance: 51 Ω)								
	Number of inputs		1 input								
	Connection method		Connector (e-CON)								
	Protection		Over voltage protection (up to a voltage of 26.4 V)								
Display	Unit*4		MPa, kPa, Pa, kgf/cm^2, bar, mbar, psi, inHg, mmHg, mmH$_2$O								
	Display type		LCD								
	Number of screens		3-screen display (Main screen, Sub screen x 2)								
	Display color		1) Main screen: Red/Green 2) Sub screen: Orange								
	Number of display digits		1) Main screen: 4 digits (7 segments) 2) Sub screen: 4 digits (Upper 1 digit 11 segments, 7 segments for other)								
	Indicator light		Lights up when switch output is turned ON. OUT1, OUT2: Orange								
Digital filter*5,*6			0, 10, 50, 100, 500, 1000, 5000 ms								
Environment	Enclosure		IP40								
	Withstand voltage		1000 VAC for 1 min between terminals and housing								
	Insulation resistance		50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing								
	Operating temperature range		Operating: 0 to 50°C, Stored: −10 to 60°C (No freezing or condensation)								
	Operating humidity range		Operating/Stored: 35 to 85% RH (No condensation)								
Standards			UL/CSA (E216656), CE/UKCA marking								
Weight	Body		25 g (Excludes power supply and output lead wires)								
	Lead wire with connector		+39 g								

∗1 Value without digital filter (at 0 ms)
∗2 If the sensor input fluctuates around the set value, the hysteresis must be set to a value more than the amount of fluctuation, or chattering will occur.
∗3 If the connected sensor does not have an extended analog output range, there is no extended analog output range available for this product.
∗4 This setting is only possible for models with the unit selection function. Only MPa, kPa, or Pa is available for models without this function (set by pressure range).
∗5 The response time indicates when the set value is 90% in relation to the step input.
∗6 Display, switch output and analog response time are affected.
∗ Products with tiny scratches, marks, or display color or brightness variations which do not affect the performance of the product are verified as conforming products.


Internal Circuits and Wiring Examples

PSE3□□A−□□□□


Output specification

Output specification	Settable circuit	Factory default settings
0	①, ②, ③, ④, ⑤, ⑥	③
1	①, ②, ③, ④, ⑤, ⑥	③
3	①, ②, ③, ④, ⑤, ⑥	④
4	①, ②, ③, ④, ⑤, ⑥	④
6	①, ②	①


①
NPN (2 outputs) + Copy function setting




②
PNP (2 outputs) + Copy function setting




③
NPN (2 outputs) + Analog voltage output setting
NPN (2 outputs) + Analog current output setting




④
PNP (2 outputs) + Analog voltage output setting
PNP (2 outputs) + Analog current output setting



⑤
NPN (2 outputs) + Auto-shift input setting



⑥
PNP (2 outputs) + Auto-shift input setting



Sensor connector connection

PSE3□□A−□□□□

Input specification


Pin no.	Terminal		
	PSE30□A (Voltage input)	**PSE31□A** (Current input)	
		Pressure sensor 2-wire type	Pressure sensor 3-wire type
1	DC (+)(Brown)	DC (–)(Brown)	DC (+)(Brown)
2	N.C.	N.C.	N.C.
3	DC (–)(Blue)	N.C.	DC (–)(Blue)
4	IN (1 to 5 V)(Black)	IN (4 to 20 mA)(Blue)	IN (4 to 20 mA)(Black)

∗ The colors in ( ) indicate the wire color of the PSE5□□ series.

Dimensions


PSE3□□A−□□□□

Option 2



A


Bracket
(Part no.: ZS-46-A1)



∗ The bracket configuration allows for mounting in four orientations.

B


Panel mount adapter
(Part no.: ZS-46-B)




Dimensions

D

Panel mount adapter + Front protection cover (Part no.: ZS-46-D)



Lead wire with connector (Part no.: ZS-46-5L)




Cable Specifications

Conductor area		0.15 mm² (AWG26)
Insulator	**O.D.**	1.0 mm
	Color	Brown, Blue, Black, White, Gray (5-core)
Sheath	**Finished O.D.**	ø3.5


Dimensions

Panel fitting dimensions


Individual mounting




Multiple (2 pcs. or more) secure mounting
<Horizontal>




Panel mount example
<Horizontal>



<Vertical>



Panel mount example
<Vertical>





3-Screen Display

Sensor Monitor

PSE300AC Series

CE UKCA RoHS

IP65

Applicable sensors					Rated pressure range	Set/Display resolution
PSE53□	PSE54□	PSE55□	PSE56□	PSE57□	−100 kPa 0 100 kPa 500 kPa 1 MPa 10 MPa	
PSE531	**PSE541**	—	**PSE561**	—	−101 kPa to 0	0.1 kPa
PSE533	**PSE543**	—	**PSE563**	**PSE573**	−100 kPa to 100 kPa	0.1 kPa
PSE530	**PSE540**	—	**PSE560**	**PSE570**	0 to 1 MPa	0.001 MPa
—	—	—	—	**PSE575**	0 to 2 MPa	0.001 MPa
—	—	—	—	**PSE576**	0 to 5 MPa	0.01 MPa
—	—	—	—	**PSE577**	0 to 10 MPa	0.01 MPa
PSE532	—	—	—	—	0 to 100 kPa	0.1 kPa
—	—	—	**PSE564**	**PSE574**	0 to 500 kPa	1 kPa
—	—	**PSE550**	—	—	0 to 2 kPa	0.001 kPa

It is possible to change the settings while checking the measured value.



Main screen
Measured value
(Current pressure value)


Sub screen
Label (Display item),
Set value (Threshold value)

Visualization of Settings

Set value (Threshold value)	P_1
Hysteresis value	H_1
Delay time	dt 1
Peak value	H_H1
Bottom value	H_Lo


Visualization of Settings

The sub screen (label) shows the item to be set.




Mode Examples

Hysteresis mode




Window comparator mode




Easy Screen Switching

It is possible to change the settings while checking the measured value.




The sub screen can be switched by pressing the up/down buttons.



* One arbitrary display mode can be added via function settings.

NPN/PNP Switch Function


The number of stock items can be reduced.



Input Range Selection (for Pressure/Flow rate)


The sensor input range can be set to the required value and displayed.
(Voltage input: 1 to 5 V/Current input: 4 to 20 mA)

Pressure switch/Flow switch can be displayed.



A is displayed for 1 V (or 4 mA).
B is displayed for 5 V (or 20 mA).
The range can be set as required.

For Digital Flow Switch for Water/PF3W511




	A	B
PF3W504	0	4
PF3W520	0	16
PF3W540	0	40
PF3W511	(0)	(100)

Set A and B to the values shown in the table above.

Simple 3-Step Setting


When the S button is pressed and the set value (P_1) is being displayed, the set value (threshold value) can be set.
When the S button is pressed and the hysteresis (H_1) is being displayed, the hysteresis value can be set.



With a snapshot function for set value reading

Pressing the and buttons for a minimum of 1 second will make the set value (threshold value) the same as the current pressure value.

Snap shot function



3-Screen Display Sensor Monitor

PSE300AC Series



How to Order

PSE3 0 0AC – AB – M –

Input specification

0	Voltage input
1	Current input

Output specification

AB	2 output type (NPN or PNP switching type)

Option (Power supply/Output lead wire)

Nil	Straight lead wire
L	Right angle lead wire
N	None

Unit specification

Nil	With unit selection function*1
M	SI unit only*2
P	With unit selection function (Initial value psi)*1

*1 Under the New Measurement Act, switches with a unit selection function are no longer allowed for use in Japan.
*2 Fixed unit: Pa, kPa, MPa

Options/Part Nos.

Description	Part no.	Note
Power supply/ output lead wire	ZS-31-B	Straight (5 m) 1 pc.
	ZS-31-C	Right angle (5 m) 1 pc.

* For details on the lead wire with M12 connector and the assembly type connector for connecting to the sensor, refer to pages 24 and 25.

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Specifications


M12 Connector Type

Series		PSE300AC								
Applicable SMC pressure sensor		PSE550	PSE531/PSE541 PSE561	PSE533/PSE543 PSE563/PSE573	PSE532	PSE564 PSE574	PSE530/PSE540 PSE560/PSE570	PSE575	PSE576	PSE577
Rated pressure range		0 to 2 kPa	0 to −101 kPa	−100 to 100 kPa	0 to 100 kPa	0 to 500 kPa	0 to 1 MPa	0 to 2 MPa	0 to 5 MPa	0 to 10 MPa
Display/Set pressure range		−0.2 to 2.1 kPa	10 to −105 kPa	−105 to 105 kPa	−10 to 105 kPa	−50 to 525 kPa	−0.105 to 1.05 MPa	−0.105 to 2.1 MPa	−0.1 to 5.25 MPa	−0.1 to 10.5 MPa
Display/Smallest settable increment		0.001 kPa	0.1 kPa	0.1 kPa	0.1 kPa	1 kPa	0.001 MPa	0.001 MPa	0.01 MPa	0.01 MPa
Electrical	**Power supply voltage**	12 to 24 VDC (±10%) with 10% voltage ripple or less								
	Current consumption	25 mA or less								
	Protection	Reverse connection protection								
Accuracy	**Display accuracy**	±0.5% F.S. ±Min. display unit (Ambient temperature of 25°C)								
	Repeatability	±0.1% F.S. ±Min. display unit (Ambient temperature of 25°C)								
	Temperature characteristics	±0.5% F.S. (Ambient temperature of 0 to 50°C, 25°C reference)								
Switch output	**Output type**	Select from NPN or PNP open collector output.								
	Output mode	Select from hysteresis mode, window comparator mode, error output or switch output OFF.								
	Switch operation	Select from normal output or reverse output.								
	Max. load current	20 mA								
	Max. applied voltage (NPN only)	30 VDC								
	Internal voltage drop (Residual voltage)	1 V or less (with load current of 20 mA)								
	Delay time *1	1 ms or less (with anti-chattering function: 20, 100, 500, 1000, 2000, 5000 ms)								
	Hysteresis	Variable from 0*2								
	Protection	Over current protection								
Sensor input	**Input type**	Voltage input: 1 to 5 VDC (Input impedance: 1 MΩ), Current input: 4 to 20 mA DC (Input impedance: 51 Ω)								
	Number of inputs	1 input								
	Connection method	M12-4 pin connector								
	Protection	Over voltage protection (up to a voltage of 26.4 VDC)								
Display	**Unit** *3	MPa, kPa, Pa, kgf/cm², bar, mbar, psi, inHg, mmHg, mmH₂O								
	Display type	LCD								
	Number of screens	3-screen display (Main screen, Sub screen x 2)								
	Display color	1) Main screen: Red/Green, 2) Sub screen: Orange								
	Number of display digits	1) Main screen: 4-digit (7-segment), 2) Sub screen: 4-digit (Upper 1-digit 11-segment, 7-segment for other)								
	Indicator light	Lights up when switch output is turned ON. OUT1/OUT2: Orange								
Digital filter *4		0, 10, 50, 100, 500, 1000, 5000 ms								
Environment	**Enclosure**	IP65								
	Withstand voltage	1000 VAC for 1 min between terminals and housing								
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing								
	Operating temperature range	Operating: 0 to 50°C, Stored: −10 to 60°C (No freezing or condensation)								
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)								
Standards		CE/UKCA								
Weight		55.4 g (without power supply or output lead wires)								


*1 Value without digital filter (at 0 ms)
*2 If the applied pressure fluctuates around the set value, the hysteresis must be set to a value more than the amount of fluctuation, or chattering will occur.
*3 This setting is only available for models with the unit selection function. Only MPa, kPa, or Pa is available for models without this function.
*4 The response time indicates when the set value is 90% in relation to the step input.

Internal Circuits and Wiring Examples


Setting of NPN open collector 2 outputs: Pressure sensor 3-wire type




Setting of PNP open collector 2 outputs: Pressure sensor 3-wire type



Setting of NPN open collector 2 outputs: Pressure sensor 2-wire type




Setting of PNP open collector 2 outputs: Pressure sensor 2-wire type



* The output type can be changed in the function selection mode.
* Numbers in the figures show the connector pin layout.


Dimensions

Power supply/Output connector pin no.





Pin no.	Description
1	DC (+)
2	OUT2
3	DC (–)
4	OUT1

Sensor connector pin no.



Pin no.	Description
1	DC (+)
2	N.C.
3	DC (–)
4	Sensor input (1 to 5 V, 4 to 20 mA)
5	N.C.







For power supply/output lead wire

Power supply/Output lead wire

ZS-31-B



ZS-31-C




Cable Specifications

Conductor	Nominal cross section	AWG23
	Outside diameter	0.72 mm
Insulator	Material	Cross-linked vinyl chloride
	Outside diameter	1.14 mm
	Number of cores	4
Sheath	Material	Oil resistant vinyl chloride
Finished outside diameter		ø4

Pin no.	Lead wire color	Description
1	Brown	DC (+)
2	White	OUT2
3	Blue	DC (–)
4	Black	OUT1

Options / Connection Examples



Lead wire and M12 connector + Assembly-type connector
Set part no.

ZS-37-A-X448	Straight 3 m	One lead wire with M12 connector and one assembly type connector are shipped together. (Not assembled)
ZS-37-B-X449	Right angle 3 m	



3-Screen Display

PSE Sensor Set Up Tool

PSE-ST Series

Applicable sensors		Rated pressure range
PSE54□-L	PSE57□-L2	−100 kPa 0 100 kPa 500 kPa 1 MPa 10 MPa
PSE541	—	**−101 kPa** **0**
PSE543	**PSE573**	**−100 kPa** **100 kPa**
—	**PSE574**	**0** **500 kPa**
PSE540	**PSE570**	**0** **1 MPa**
—	**PSE575**	**0** **2 MPa**
—	**PSE576**	**0** **5 MPa**
—	**PSE577**	**0** **10 MPa**

Selectable from 2 models of IO-Link compatible compact pressure switch



Compact Pneumatic Pressure Sensor
PSE54□-L





Pressure Sensor for General Fluids
PSE57□-L2


* Similar 2 in 1 Auto Switch Setup Tool D-MH2E is not available for these sensors.

Connection sensor detection

Automatic range detection and display!




PSE570-L2





PSE577-L2





Simple copy function


Easy to create copies!




SMC

Simple 3-Step Setting

When the S button is pressed and the set value (P_1) is being displayed, the set value (threshold value) can be set.
When the S button is pressed and the hysteresis (H_1) is being displayed, the hysteresis value can be set.



Now with a snap shot function for set value reading



Mobile Battery Connection



* The mobile battery and USB cable should be provided by the customer.

Other Settings and Functions

Function	Description
PNP/NPN switching	The switch output can be changed between PNP and NPN.
Digital filter	The digital filter can be added to filter the pressure measurement.
Copy function	Pressure switch settings can be copied.
Initial settings	If the setting of the pressure switch becomes unclear, it can be restored to its initial state.
Zero-clear	This function clears and resets the zero value on the display of measured pressure.
Locator function	By turning the function ON, it is possible to make the LED of the connected pressure switch flash.

Set up flow and configurable functions

3 Step Setting Mode

- Threshold value setting
  or
- Hysteresis value setting

Function Selection Mode

- Output mode setting
- Comparator output setting
- Normal/Reversed setting
- Threshold value setting
- Hysteresis value setting
- ON delay time selection
- OFF delay time selection

Simple ← **Settings** → Higher function


1 Mode selection



Press the button once.



Press the button for 2 s or longer.



All settings reference mode | Function selection mode | Locator mode

Function selection mode selection



2 Output mode selection

Selection from
- Comparator output
- Error output
- Output OFF.

3 Comparator output setting

Selection from
- Hysteresis mode
- Window comparator mode.



4 Normal/Reversed setting

Selection from
- Normal output
- Reversed output.



5 Set value (Threshold value) setting

- Adjust the numerical value.





6 Hysteresis value setting

- Adjust the numerical value.



7 ON delay time setting

- Adjust the numerical value.



8 OFF delay time setting

- Adjust the numerical value.



Completion of Setting | **Completion of Setting**

SMC

3-Screen Display **PSE Sensor Set Up Tool**

PSE-ST Series



How to Order

PSE−ST−□

Connector converter

Symbol	Description
Nil	Without connector converter
L	Connector for separate line
S	M12 4-pin socket connector

Connector Converter Part Nos.

M12 4-pin socket connector	**D-LH03B**
Connector for separate line	**D-LH03C**

PSE54□ Series PSE57□ Series

For common precautions and specific product precautions regarding pressure switch specifications, wiring, and other details, refer to the "Operation Manual" on the SMC website.

Specifications


Model		PSE-ST						
Applicable pressure sensor		PSE541-L	PSE543-L PSE573-L2	PSE574-L2	PSE540-L PSE570-L2	PSE575-L2	PSE576-L2	PSE577-L2
Pressure	**Rated pressure range**	0 to −101 kPa	−100 to 100 kPa	0 to 500 kPa	0 to 1 MPa	0 to 2 MPa	0 to 5 MPa	0 to 10 MPa
	Display/ set pressure range	10 to −105 kPa	−105 to 105 kPa	−50 to 525 kPa	−0.105 to 1.05 MPa	−0.105 to 2.1 MPa	−0.105 to 5.25 MPa	−0.105 to 10.5 MPa
Electrical	**Power supply voltage**	5 VDC						
	Current consumption	2 A or less						
	Protection	Over voltage protection						
	Supply connector	USB Type-C						
Sensor input	**Number of inputs**	1						
	Connection method	Connector						
	Protection	Polarity protection, Over current protection						
Display	**Display type**	LCD						
	Number of screens	3-screen display (Main screen, Sub screen x 2)						
	Display color	1) Main screen: Red/Green 2) Sub screen: Orange						
	Number of display digits	1) Main screen: 4 digits (7 segments) 2) Sub screen: 4 digits (Upper 1 digit 11 segments, 7 segments for other)						
Environment	**Enclosure**	IP40						
	Withstand voltage	1000 VAC for 1 min between terminals and housing						
	Insulation resistance	50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing						
	Operating temperature range	Operating: 0 to 45°C, Stored: −10 to 60°C (No freezing or condensation)						
	Operating humidity range	Operating/Stored: 35 to 85% RH (No condensation)						
Standards		CE/UKCA/WEEE						
Weight	**Body**	50 g (Excludes connector converter)						

* Use this product by connecting it to a mobile battery with a 5 VDC, 2 A minimum output.
* Depending on the type of mobile battery, it may not operate.
* Do not connect to any power source other than a mobile battery. If the product does not operate, there is a risk that the power supply may be faulty.
* If this product is connected to a mobile battery that has a function that automatically turns off the power supply according to the current consumption of the mobile battery, this product may not operate correctly.
* Products with tiny scratches, marks, or display color or brightness variations which do not affect the performance of the product are verified as conforming products.

PSE54□ Series PSE57□ Series

For common precautions and specific product precautions regarding pressure switch specifications, wiring, and other details, refer to the "Operation Manual" on the SMC website.


Connection Method



Connector Conversion Parts Pin Layout

D-LH03B

Pin no.	Description
1	DC (+)
2	N.C.
3	DC (–)
4	OUT1




D-LH03C

Connector colour	Description
Red	DC (+)
Black	OUT1
Blue	DC (–)


Dimensions

PSE-ST body




Connector converter


D-LH03B



D-LH03C



View A



⚠ Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of **"Caution," "Warning"** or **"Danger."** They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)*1), and other safety regulations.

⚠ Danger : **Danger** indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.

⚠ Warning: **Warning** indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.

⚠ Caution: **Caution** indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.

*1) ISO 4414: Pneumatic fluid power - General rules and safety requirements for systems and their components
ISO 4413: Hydraulic fluid power - General rules and safety requirements for systems and their components
IEC 60204-1: Safety of machinery - Electrical equipment of machines - Part 1: General requirements
ISO 10218-1: Robots and robotic devices - Safety requirements for industrial robots - Part 1:Robots
etc.

⚠ Warning

1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalog information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

2. Only personnel with appropriate training should operate machinery and equipment.

The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.

3. Do not service or attempt to remove product and machinery/ equipment until safety is confirmed.

1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.

4. Our products cannot be used beyond their specifications. Our products are not developed, designed, and manufactured to be used under the following conditions or environments. Use under such conditions or environments is not covered.

1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
2. Use for nuclear power, railways, aviation, space equipment, ships, vehicles, military application, equipment affecting human life, body, and property, fuel equipment, entertainment equipment, emergency shut-off circuits, press clutches, brake circuits, safety equipment, etc., and use for applications that do not conform to standard specifications such as catalogs and operation manuals.
3. Use for interlock circuits, except for use with double interlock such as installing a mechanical protection function in case of failure. Please periodically inspect the product to confirm that the product is operating properly.

⚠ Caution

We develop, design, and manufacture our products to be used for automatic control equipment, and provide them for peaceful use in manufacturing industries.
Use in non-manufacturing industries is not covered.
Products we manufacture and sell cannot be used for the purpose of transactions or certification specified in the Measurement Act.
The new Measurement Act prohibits use of any unit other than SI units in Japan.

Limited warranty and Disclaimer/ Compliance Requirements

The product used is subject to the following "Limited warranty and Disclaimer" and "Compliance Requirements".
Read and accept them before using the product.

Limited warranty and Disclaimer

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered, whichever is first.*2)
   Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.
2. For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided.
   This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalog for the particular products.

***2) Vacuum pads are excluded from this 1 year warranty.**
A vacuum pad is a consumable part, so it is warranted for a year after it is delivered.
Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

Compliance Requirements

1. The use of SMC products with production equipment for the manufacture of weapons of mass destruction (WMD) or any other weapon is strictly prohibited.
2. The exports of SMC products or technology from one country to another are governed by the relevant security laws and regulations of the countries involved in the transaction. Prior to the shipment of a SMC product to another country, assure that all local rules governing that export are known and followed.

Revision History

Edition B	* A DIN rail/terminal block type and current input type have been added to the PSE300 series.	LT
Edition C	* The PSE570 series pressure sensor for general fluids has been added. * The number of pages has been decreased from 40 to 36.	TT
Edition D	* An IO-Link compatible switch output specification has been added to the PSE540 series. * An IO-Link compatible switch output specification has been added to the PSE570 series. * The number of pages has been increased from 36 to 60.	

⚠ Safety Instructions Be sure to read the "Handling Precautions for SMC Products" (M-E03-3) and "Operation Manual" before use.

SMC Corporation
Akihabara UDX 15F,
4-14-1, Sotokanda, Chiyoda-ku, Tokyo 101-0021, JAPAN
Phone: 03-5207-8249 Fax: 03-5298-5362
https://www.smcworld.com

© 2024 SMC Corporation All Rights Reserved

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.